



TORO REELMASTER 5510D

The Reelmaster® 5510 features 7-inch Dual Precision Adjustment (DPA) cutting units to deliver an exceptional quality-of-cut and after-cut appearance. The Reelmaster 5510 includes a powerful Tier 4-compliant diesel engine that can be equipped with our exclusive CrossTrax® all-wheel drive system for exceptional power and control.

Excellent operator comfort and outstanding serviceability are already included in each of the industry-leading Reelmaster 5010 Series models.

- Improved access to routine service points and service components, along with a robust machine design, results in less frequent maintenance intervals and less time is required to perform maintenance tasks.
- The Reelmaster is powered by a 36.8 hp (27.5 kW) Yanmar® diesel engine that includes an exhaust after-treatment system that ensures machine emissions meet the EPA requirements and that your course can do its part for the environment.
- Optimized design and use of lightweight materials means less weight and turf compaction without sacrificing performance and functionality.
- All of the indicators and controls to operate the unit are conveniently located on the right armrest. Control console pivots back for right hand entry and exit. Tilt steering, deluxe suspension seat, improved visibility and lower operating noise enhance the operator experience and help to reduce fatigue.
- Dual Precision Adjustment (DPA) cutting units - featuring Toro's EdgeSeries™ reels combine to deliver a consistent, high quality cut and superior after cut appearance, while reducing maintenance with improved reel edge retention.
- **Two options to choose from: 03954 with 36.8 hp (27.5 kW) Yanmar® diesel engine or 03964 with Kubota® 35.5 hp (26.5 kW) diesel engine.**



Specifications:

MODELS	03954 - 36.8 hp (27.5 kW) Yanmar® diesel engine 03964 - Kubota® 35.5 hp (26.5 kW) diesel engine.	ELECTRICAL SYSTEM	Heavy-duty 12-volt battery, 570 CCA, 40 amp alternator. Electronic control unit is a microprocessor based, solid state control unit with diagnostic capabilities.
BATTERY	12V	ENGINE COOLING	Liquid Cooled
BLADE TYPE	EdgeSeries™ DPA radial or forward swept reels.	FUEL CAPACITY	03954 - 53 L 03964 - 51.1 L
CLIP	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200 - 1,650 rpm with a backlap speed of 200 rpm.	FUEL FILTER	Replaceable spin-on fuel filter/water separator.
FREQUENCY/BACKLAPPING	Standard on-board backlapping.	GROUND SPEED	Forward: 0 - 16.1 km/h Reverse: 0 - 6.4 km/h
COOLING SYSTEM	03954 - Plate and bar radiator/oil cooler combination, 6.3 fins per inch, 10 quart (9.5 liter) capacity. 03964 - Rear mounted radiator with industrial tube and fin construction, 6.5 fins per inch, 6.6 litre capacity.	HEIGHT OF CUT	6.4 mm - 38.1 mm
CUTTING UNIT ACCESSORIES	Rear Roller Brush Kit, Universal Groomer, Broomer, Grass Baskets	HYDRAULIC FLUID TYPE	Toro PX™ Extended Life Hydraulic Fluid
CUTTING UNIT LIFT/LOWER	Hydraulic - front and rear cutting unit lift/lowers are sequenced for uniform starting and ending points.	OIL CAPACITY	4.7 L
CUTTING UNIT TYPE/CONFIGURATION	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.	STEERING SYSTEM	Rear wheel, power steering with an independent hydraulic pump and circuit.
DRIVETRAIN	Hybrid	TRACTION DRIVE	Front drive wheels powered by a hydrostatic pump with individual wheel motors. All-wheel drive optional with CrossTrax® All-Wheel Drive system, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.

QUALITY BRANDS, EXCEPTIONAL SERVICE.

