

**parkland**



## TORO WORKMAN GTX

## LITHIUM-ION TRUCK

The Workman GTX is a grounds and turf crossover vehicle that boasts an unequalled combination of comfort, utility and control, making it simply superior to the competition.

It's increased power, improved steering and exclusive suspension and braking systems make the Workman GTX the most versatile, practical and comfortable utility vehicle in its class.

The lithium-ion technology powering the new Workman GTX Lithium-Ion is built to deliver hours of reliable performance. It's the largest lithium-ion model in its class, so it can handle big jobs. At nearly 400 pounds (181.4 kg) lighter than traditional Workman GTX models, it makes a big impression on productivity without leaving a big impression on turf. The lithium-ion power packs are maintenance-free and have a long lifespan, so the machine is always ready to get to work.

So whether you are setting cups, checking on irrigation, working around campus, or moving people or materials, the Workman GTX has the power and versatility to get the job done right.



**QUALITY BRANDS, EXCEPTIONAL SERVICE.**

**parkland.co.nz**





## Specifications:

**Model: 07413TC**

<b>POWER SYSTEM</b>	48V brushless AC induction drive	<b>CONTROLLER</b>	540 amps max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes
<b>STEERING</b>	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter	<b>CHARGER</b>	On-board high efficiency 900W smart charger. AC Input Voltage: 100-240 VAC AC Input Frequency: 50/60 Hz Max AC Input Current: 10 A
<b>TURNING RADIUS</b>	Turning clearance circle: 20.7' (6.3 m), inside turning radius: 60.25" (153 cm)	<b>REEL SPEED</b>	Adjustable - 1000 RPM max
<b>BRAKES</b>	Front and rear wheel hydraulic disc brakes	<b>TRACTION DRIVE</b>	Series / Parallel 3WD
<b>SUSPENSION</b>	Front - Modified MacPherson Strut Rear - Articulating Swing Arm. Adjustable coil over shocks at all four wheels	<b>ELECTRIC MOTOR</b>	Brushless high-torque AC Induction motor with 5.0kW continuous power
<b>SUSPENSION TRAVEL</b>	Front Suspension Travel: 3.5" Rear Suspension Travel: 4"	<b>TEMPERATURE REQUIREMENTS</b>	Storage: -30 to 45°C (3 months); 145 to 60°C (1 month) Charging: Normal Charge (Full Current): 5 to 45°C; Pre Charge (Half Current): -10 to 5°C and 45 to 60°C Operation: -20 to 60°C
<b>GROUND SPEED</b>	16 mph (25.6 km/h), adjustable	<b>VEHICLE CAPACITY</b>	2-seat with bed 544 kg
<b>TRANSAXLE</b>	11.47:1 Forward, 14.35:1 Reverse	<b>TOWING CAPACITY</b>	680 kg Class 1 - 1.25" receiver standard.
<b>GROUND CLEARANCE</b>	Front: 12" (30.4 cm) Rear: 7" (17.8 cm)	<b>CAB DIMENSIONS INSTALLED</b>	Height: 82" (208 cm) Width: 56" (142 cm)
<b>BATTERIES</b>	Four Lithium-Ion Samsung® SDI batteries. 48V nominal		

**2 Year Warranty**

QUALITY BRANDS, EXCEPTIONAL SERVICE.

