

TORO®

2023-2024 TORO® TITAN® TINES





PLAN YOUR AERATION SCHEDULE TODAY

Contact your local Toro distributor

TABLE OF CONTENTS

INTRODUCTION	1-2
A TINE TO FIT EVERY APPLICATION	2
SELECTION AND MEASUREMENT GUIDE	3
TINE HEAD IDENTIFICATION GUIDE	4
AERATION EVALUATION GUIDE	5-8
PROCORE® 648s	9-13
PROCORE 864/1298	14-18
PROCORE 440/660/880	19-22
GREENS AERATOR	23-25
FAIRWAY AERATOR	26-29
TURF AERATOR 686/687	30
PROCORE SR SERIES	31-39
SR48	32
SR54	33
SR54-S	34
SR70	35
SR70-S	36
SR72	37
SR75	38-39
TITAN® TINE CONVERSION SLEEVES	40
TITAN TINES FOR COMPETITIVE MODELS	40-44
QUICK REFERENCE	47-50

EXACT STANDARDS



AERATION IMPROVES TURF CONDITIONS

Aeration keeps your turf looking great. It's important to aerate often, especially when it comes to high traffic areas, and with TITAN® TINES on your team you'll know that you have the best equipment to meet all of your aeration needs successfully.

TORO'S FAMILY OF TINES ARE DESIGNED TO MEET YOUR EXACT AERATION NEED

TINE	TIP	LONGEVITY	APPLICATION	WALL THICKNESS
Toro Classic	Standard durable heat-treated tip	Good	Good quality in most turf conditions	Thin wall delivers durability and exceptional performance
TITAN	Sharp heat-treated tip for improved hole quality and life	Better	Provides superior performance and long-lasting wear in most turf conditions	Thin wall delivers durability and exceptional performance
TITAN Max	Sharp carbide tip for excellent hole quality and life	Best	Provides superior performance and long-lasting wear in most conditions	Thin wall delivers durability and exceptional performance
TITAN Fairway	Standard heat-treated fairway tip for consistent core removal	Better	Provides quality performance in natural soil conditions	Thicker wall provides good hole quality and maximum strength
TITAN HD Fairway	Enhanced hardened tip for 75% longer life than TITAN Fairway	Best	Provides excellent performance and wear in extreme conditions	Thicker wall provides good hole quality and maximum strength


A TINE TO FIT EVERY APPLICATION

Toro® has just about every possible tine you can imagine for the changing seasons and your most demanding turf conditions. TITAN® tines offer superior quality to provide your grounds with the best possible care.


Jump-start your productivity with the TITAN QuickChange™ tine head. The patent-pending taper-lock design makes changing tines a snap. In fact, many users have reduced set-up time by up to 75%. TITAN QuickChange will help you get your aeration done FAST!

TORO TITAN TINES OFFER

- Over 150 tines, providing multiple aeration choices
- A wide variety of types to meet your exact aeration requirements
- Higher productivity: TITAN Max designed with long-lasting tungsten carbide blend tip
- Better performance: TITAN tines last approximately 3–4 times longer than standard tines
- An optimised core, removing more thatch for maximum topdressing
- A superior hole, improving recovery time and maintaining playability




CORING TINES




SOLID TINES




SELECTION AND MEASUREMENT




PROCORE 648/648s/864/1298 (see pages 9–18)


QUAD TINE HEAD (1x6)


Tine mount	5/16" (9.5 mm)
Qty of tines	6


QUAD TINE HEAD (2x5)


Tine mount	5/16" (9.5 mm)
Qty of tines	10


3/4" 3-TINE HEAD


Tine mount	3/4" (19 mm)
Qty of tines	3


3/4" 4-TINE HEAD


Tine mount	3/4" (19 mm)
Qty of tines	4


QUICKCHANGE 3-TINE HEAD


Tine mount	3/4" (19 mm) or 7/8" (22.2 mm)
Qty of tines	3


QUICKCHANGE 4-TINE HEAD

Tine mount	3/4" (19 mm) or 7/8" (22.2 mm)
Qty of tines	4



7/8" 3-TINE HD HEAD

Tine mount	7/8" (22.2 mm)
Qty of tines	3



NEEDLE TINE HEAD

Tine mount	Needle
Qty of tines	5


PROCORE 440/660/880 (see pages 19–22)


QUAD TINE HEAD (1x6)


Tine mount	5/16" (9.5 mm)
Qty of tines	8


NEEDLE TINE HEAD


Tine mount	Needle
Qty of tines	6


3/4" 3-TINE HEAD


Tine mount	3/4" (19 mm)
Qty of tines	3


3/4" 4-TINE HEAD

Tine mount	3/4" (19 mm)
Qty of tines	4


7/8" 3-TINE HEAD

Tine mount	7/8" (22.2 mm)
Qty of tines	3


7/8" 4-TINE HEAD

Tine mount	7/8" (22.2 mm)
Qty of tines	4


PROCORE SR SERIES (see pages 31–39)


SR54-S / SR70-S


Tine mount	5/16" (7.9 mm) or 12.0 mm
Qty of tines	3 or 4


SR54 / SR70

Tine mount	5/16" (7.9 mm) or 12.0 mm
Qty of tines	2 or 3


SR48 / SR72

Tine mount	5/16" (7.9 mm), 12.0 mm or 18 mm
Qty of tines	3 or 4


SR75

Tine mount	5/16" (7.9 mm) or 12.0 mm
Qty of tines	2 or 3



TINE SELECTION CHART:

- Speed and ease of use
- Selection of proper turf guard based on aerator and tine configuration needs.
- Quickly identify the amount of soil removed and the percentage of surface area affected.

AERATION EVALUATION GUIDE WITH TINE SELECTION CHART

When you're looking to keep your golf course and grounds in top shape, you need a system that helps you quickly choose the right treatment for your turf needs.

Aeration is the key and the tine selection chart offers you fast answers that convey exactly what you need to do to keep your turf looking great.

The tine selection guide makes it easy to choose and understand the right solution for your golf course and ground needs.



Preparing for step one: find your model number

MODEL CONFIGURATION				
Product	Description No	No	Lateral spacing options	Forward spacing options
ProCore 648/648s Model 09960	Needle tine head Quad tine head, 2 rows of 5 Quad tine head, 1 row of 6 3-tine, $\frac{3}{4}$ " (19 mm) mount head 4-tine, $\frac{3}{4}$ " (19 mm) mount head 3-tine HD, $\frac{3}{8}$ " (22.2 mm) mount head 4-tine Titan QuickChange 3-tine Titan QuickChange	09739 09736 09737 09794 09796 09797 09719 09711	1.60" (4.1 cm) 1.60" (4.1 cm) 1.30" (3.3 cm) 2.60" (6.6 cm) 2.0" (5.1 cm) 2.60" (6.6 cm) 2.0" (5.1 cm) 2.60" (6.6 cm)	09960 has hole spacing in 0.25" increments from 1" – 4.5" 1.5, 2, 2.5" (3.8; 5.1; 6.4 cm) 2.5" (6.4 cm) 1.5, 2, 2.5, 3" (3.8; 5.1; 6.4; 7.6 cm)
ProCore 864/1298 Models 09715, 09716				
ProCore 440/660/880 Models 09701, 09702	Needle tine head 660/880 Needle tine head 660/880 Quad tine head 3-tine, $\frac{3}{4}$ " (19.0 mm) mount head 4-tine, $\frac{3}{4}$ " (19.0 mm) mount head 3-tine, $\frac{3}{8}$ " (22.2 mm) mount head 4-tine, $\frac{3}{8}$ " (22.2 mm) mount head	09720 09720 09721 09722 09723 09733 09734	1.20" (3.0 cm) 1.20" (3.0 cm) 1.20" (3.0 cm) 3.20" (8.1 cm) 2.40" (6.1 cm) 3.20" (8.1 cm) 2.40" (6.1 cm)	1.5, 2, 2.5" (3.8; 5.1; 6.4 cm) 1.5, 2, 2.5" (3.8; 5.1; 6.4 cm) 1.5, 2, 2.5" (3.8; 5.1; 6.4 cm) 2, 2.5, 3, 3.5, 4, 4.5" (5.1; 6.4; 7.6; 8.9; 10.2; 11.4 cm) 2, 2.5, 3, 3.5, 4, 4.5" (5.1; 6.4; 7.6; 8.9; 10.2; 11.4 cm) 2, 2.5, 3, 3.5, 4, 4.5" (5.1; 6.4; 7.6; 8.9; 10.2; 11.4 cm) 2, 2.5, 3, 3.5, 4, 4.5" (5.1; 6.4; 7.6; 8.9; 10.2; 11.4 cm)
Toro greens aerator Models 09110, 09120	$\frac{3}{4}$ " (19.0 mm) head $\frac{3}{8}$ " (22.2 mm) head Needle head $\frac{3}{8}$ " z head	59-2500 62-4610 94-3421 94-3420	2.25" (5.7 cm)	2.5" (6.4 cm)
Toro fairway aerator Models 09500, 09501, 09502	—	—	3.5" (8.9 cm) 5.25" (13.3 cm)	3.0, 6.0" (7.6; 15.2 cm) 3.0, 6.0" (7.6; 15.2 cm)

* Tine depth can vary based on machine set-up.

DETERMINE THE TOTAL SURFACE AREA AFFECTED AND THE AMOUNT OF MATERIAL REMOVED

STEP ONE

FIND HOLES PER SQUARE FOOT (METRE)

If you know your lateral and forward spacing, see the 'Holes per square (foot) metre' table.

If you are not sure of your forward and lateral spacing, but know your aerator model number, use the Preparing for step one chart on the previous page and pick your spacing options. This table will also help you determine the proper turf holder based on your tine configuration.

Step one example:

- Lateral spacing = 2" (5.1 cm)
- Forward spacing = 2" (5.1 cm)
- Holes per square foot (metre) = 36 (384.5)

ALL MODELS	FORWARD SPACING IN INCHES (CENTIMETRES)								
	1 (2.5)	1.5 (3.8)	2 (5.1)	2.5 (6.4)	3 (7.6)	3.5 (8.9)	4 (10.2)	4.5 (11.4)	6 (15.2)
LATERAL SPACING	HOLES PER SQUARE FOOT (METRE)								
1.2 (3.0)	120 (1333.3)	80 (877.2)	60 (653.6)	48 (520.8)	40 (438.6)	34.3 (374.5)	30 (326.8)	26.7 (292.4)	-
1.33 (3.3)	-	72 (797.4)	54.1 (594.2)	43.3 (473.5)	36 (398.7)	-	-	-	-
1.6 (4.1)	-	-	-	(381.1)	-	-	-	-	-
2 (5.1)	72 (784.3)	48 (516.0)	36 (384.5)	28.8 (306.4)	24 (258.0)	-	-	-	-
2.25 (5.7)	-	-	-	25.6 (274.1)	-	-	-	-	-
2.4 (6.1)	60 (655.7)	40 (431.4)	30 (321.4)	24 (256.1)	20 (215.7)	17.1 (184.2)	15 (160.7)	13.3 (143.8)	-
2.5 (6.4)	57.6 (625.0)	38.4 (411.2)	28.8 (306.4)	23 (244.1)	19.2 (205.6)	-	-	-	-
3.2 (8.1)	45 (493.8)	30 (324.9)	22.5 (242.1)	18 (192.9)	15 (162.4)	12.9 (138.7)	11.3 (121.0)	10 (108.3)	-
3.5 (8.9)	-	-	-	-	13.7 (147.8)	-	-	-	-
5.25 (13.3)	-	-	-	-	-	-	-	-	4.6 (49.5)


STEP TWO

DETERMINE THE TOTAL SURFACE AREA AFFECTED AND VOLUME OF SOIL REMOVED

To determine the total surface area affected and volume of soil removed when aerating, please see the **Percentage of surface area affected and amount of volume removed** table. All you need to know is holes per square foot (metre), core diameter (ID) and the depth* at which you are aerating.

Step two example:

- Holes per square foot (metre) = 36 (232.3)
- Core diameter = 0.300" (0.8 cm)
- Depth = 3.0" (7.6 cm)
- Percentage of surface area affected = 1.77%
- Volume removed = 4.42 cu-feet per 1,000 sq/ft (0.133 cubic metres per 100 square metres)



Percentage of surface area affected and amount of volume removed

Core diameter depth*	Holes per square foot (metre) in inches (centimetres)																																	
	4.6 (49.5)	10 (108.3)	11.3 (121.0)	12.9 (138.7)	13.3 (143.8)	13.7 (147.8)	15 (162.4)	17.1 (184.2)	18 (192.9)	19.2 (205.6)	20 (215.7)	22.5 (242.1)	23 (244.1)	24 (256.1)	25.6 (274.1)	26.7 (292.4)	28.8 (306.4)	30 (321.4)	34.3 (374.5)	36 (384.5)	38.4 (411.2)	40 (431.4)	43.3 (473.5)	45 (493.8)	48 (516.0)	54.1 (594.2)	57.6 (625.0)	60 (655.7)	72 (784.3)	80 (877.2)	120 (1333.3)			
0.2 (0.5)	0.10%	0.22%	0.25%	0.28%	0.29%	0.30%	0.33%	0.37%	0.39%	0.42%	0.44%	0.49%	0.50%	0.52%	0.56%	0.58%	0.63%	0.65%	0.75%	0.79%	0.84%	0.87%	0.94%	0.98%	1.05%	1.18%	1.23%	1.48%	1.57%	1.64%	1.75%	1.86%	2.37%	
1.5 (3.8)	0.12 (0.004)	0.27 (0.008)	0.31 (0.009)	0.35 (0.011)	0.36 (0.011)	0.37 (0.011)	0.41 (0.013)	0.47 (0.014)	0.49 (0.015)	0.52 (0.016)	0.55 (0.017)	0.61 (0.019)	0.63 (0.019)	0.65 (0.020)	0.7 (0.021)	0.73 (0.023)	0.79 (0.024)	0.82 (0.025)	0.93 (0.030)	0.98 (0.033)	1.05 (0.032)	1.09 (0.033)	1.18 (0.036)	1.23 (0.038)	1.48 (0.046)	1.57 (0.048)	1.64 (0.051)	1.75 (0.040)	1.86 (0.060)	2.18 (0.068)	2.27 (0.070)			
2 (5.1)	0.17 (0.005)	0.36 (0.011)	0.41 (0.014)	0.47 (0.014)	0.48 (0.015)	0.5 (0.015)	0.55 (0.017)	0.62 (0.019)	0.65 (0.020)	0.7 (0.021)	0.73 (0.022)	0.82 (0.025)	0.93 (0.026)	0.97 (0.030)	1.05 (0.032)	1.25 (0.039)	1.31 (0.040)	1.4 (0.043)	1.45 (0.045)	1.57 (0.049)	1.64 (0.051)	1.7 (0.053)	2.09 (0.065)	2.18 (0.068)	2.62 (0.081)	2.91 (0.091)	4.3 (0.138)	5.14 (0.138)	5.21 (0.138)	5.3 (0.138)	5.4 (0.138)	5.5 (0.138)		
2.5 (6.4)	0.21 (0.006)	0.45 (0.014)	0.51 (0.013)	0.58 (0.018)	0.61 (0.019)	0.62 (0.019)	0.68 (0.021)	0.78 (0.024)	0.82 (0.025)	0.87 (0.027)	0.91 (0.028)	1.02 (0.031)	1.05 (0.032)	1.09 (0.033)	1.16 (0.036)	1.21 (0.038)	1.31 (0.040)	1.36 (0.042)	1.56 (0.049)	1.64 (0.050)	1.75 (0.053)	1.82 (0.056)	1.97 (0.061)	2.05 (0.064)	3.05 (0.067)	3.48 (0.077)	3.62 (0.085)	3.73 (0.085)	3.77 (0.085)	3.84 (0.085)	3.95 (0.085)			
3 (7.6)	0.25 (0.008)	0.55 (0.017)	0.61 (0.015)	0.7 (0.021)	0.73 (0.022)	0.75 (0.023)	0.82 (0.025)	0.93 (0.030)	1.05 (0.032)	1.09 (0.033)	1.23 (0.037)	1.26 (0.038)	1.31 (0.039)	1.4 (0.042)	1.45 (0.045)	1.57 (0.047)	1.64 (0.050)	1.87 (0.058)	1.96 (0.059)	2.09 (0.063)	2.18 (0.066)	2.38 (0.073)	2.45 (0.076)	3.49 (0.092)	3.75 (0.103)	3.84 (0.103)	3.93 (0.121)	4.36 (0.125)	5.54 (0.125)	6.54 (0.125)	6.6 (0.125)	6.65 (0.125)	6.7 (0.125)	
3.5 (8.9)	0.29 (0.009)	0.64 (0.020)	0.72 (0.028)	0.82 (0.025)	0.85 (0.026)	0.87 (0.027)	0.95 (0.029)	1.09 (0.033)	1.15 (0.035)	1.22 (0.037)	1.43 (0.044)	1.47 (0.044)	1.53 (0.046)	1.63 (0.049)	1.7 (0.053)	1.83 (0.055)	1.91 (0.058)	2.18 (0.068)	2.29 (0.069)	2.44 (0.074)	2.55 (0.078)	2.78 (0.085)	2.86 (0.089)	3.44 (0.107)	3.67 (0.113)	3.82 (0.118)	4.58 (0.141)	5.09 (0.158)	7.64 (0.241)	7.73 (0.241)	7.82 (0.241)	7.92 (0.241)	8.05 (0.241)	8.18 (0.241)
4 (10.2)	0.33 (0.010)	0.73 (0.022)	0.82 (0.029)	0.93 (0.029)	0.97 (0.030)	1 (0.031)	1.09 (0.034)	1.25 (0.038)	1.31 (0.040)	1.45 (0.045)	1.64 (0.050)	1.68 (0.050)	1.75 (0.053)	1.86 (0.057)	1.94 (0.060)	2.09 (0.063)	2.18 (0.066)	2.49 (0.077)	2.79 (0.085)	2.91 (0.089)	3.15 (0.098)	3.27 (0.107)	3.47 (0.123)	4.19 (0.129)	4.36 (0.136)	5.24 (0.162)	5.42 (0.162)	5.82 (0.162)	5.88 (0.162)	6.16 (0.162)	6.2 (0.162)	6.28 (0.162)	7.83 (0.276)	
0.3 (0.8)	0.22%	0.49%	0.55%	0.63%	0.65%	0.67%	0.74%	0.84%	0.88%	0.94%	0.98%	1.01%	1.13%	1.26%	1.31%	1.41%	1.47%	1.68%	1.77%	1.88%	1.96%	2.13%	2.21%	2.36%	2.83%	2.95%	3.53%	3.93%	5.89%	5.95%	6.26%	6.75%	7.85%	8.28%

PROCORE® 648/648s



TINE HEADS AND TURF GUARDS

TINE HEADS		TIMES REQ'D		TURF GUARDS		
Description	Part No	Qty	Part No	Qty	Part No	Qty
Needle tine head	09739	30	120-1047	2	120-1052	1
Quad tine $\frac{3}{8}$ " mount head, 2 rows of 5	09736	60	120-1047	2	120-1052	1
Quad tine $\frac{3}{8}$ " mount head, 1 row of 6	09737	36	120-1050	2	120-1053	1
3-tine, $\frac{3}{8}$ " mount head	09794	18	120-1044	2	110-4358	1
4-tine, $\frac{3}{8}$ " mount head	09796	24	120-1045	2	120-1046	1
3-tine HD, $\frac{3}{8}$ " mount head	09797	18	120-1044	2	110-4358	1
3-tine, Titan $\frac{3}{8}$ " or $\frac{5}{16}$ " mount QuickChange head	09711	18	120-1044	2	110-4358	1
4-tine, Titan $\frac{3}{8}$ " or $\frac{5}{16}$ " mount QuickChange head	09719	24	120-1045	2	120-1046	1



$\frac{3}{8}$ " (9.5 MM) MOUNT

TITAN QUAD	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	108-9104
	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	108-9105
	4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9106
	4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	108-9293
	5.00" (127.0 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	138-5937
	5.00" (127.0 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	137-6526
	5.00" (127.0 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	137-6527
	5.00" (127.0 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	137-6529
	5.50" (139.7 mm)	0.41" (10.3 mm)	0.55" (14.7 mm)	0.063" (1.6 mm)	108-9290
	4.50" (114.3 mm)	-	0.20" (5.1 mm)	-	108-9230
	4.50" (114.3 mm)	-	0.25" (6.3 mm)	-	108-9231
	4.50" (114.3 mm)	-	0.30" (7.6 mm)	-	108-9232
	4.50" (114.3 mm)	-	0.38" (9.7 mm)	-	108-9233
	5.50" (139.7 mm)	-	0.20" (5.1 mm)	-	108-9234
	5.50" (139.7 mm)	-	0.25" (6.3 mm)	-	108-9235
	5.50" (139.7 mm)	-	0.30" (7.6 mm)	-	108-9236
	5.50" (139.7 mm)	-	0.38" (9.7 mm)	-	108-9237
	5.00" (127.0 mm)	-	0.63" (15.9 mm)	-	108-9238
	4.50" (114.3 mm)	-	0.38" (9.5 mm)	-	108-9215
	4.50" (114.3 mm)	-	0.50" (12.7 mm)	-	108-9216
	4.50" (114.3 mm)	-	0.63" (15.9 mm)	-	108-9217
	5.50" (139.7 mm)	-	0.38" (9.5 mm)	-	108-9218
	5.50" (139.7 mm)	-	0.50" (12.7 mm)	-	108-9219
	5.50" (139.7 mm)	-	0.63" (15.9 mm)	-	108-9220

$\frac{3}{4}$ " (19.0 MM) MOUNT

TITAN HOLLOW	HOLLOW MAX
	4.75" (120.6 mm) 0.28" (7.1 mm) 0.46" (11.7 mm) 0.058" (1.5 mm) 108-9128
	4.75" (120.6 mm) 0.41" (10.3 mm) 0.56" (14.2 mm) 0.058" (1.5 mm) 108-9129
	4.75" (120.6 mm) 0.53" (13.4 mm) 0.66" (16.8 mm) 0.058" (1.5 mm) 108-9130
	5.75" (146.0 mm) 0.28" (7.1 mm) 0.46" (11.7 mm) 0.058" (1.5 mm) 108-9132
	5.75" (146.0 mm) 0.41" (10.3 mm) 0.56" (14.2 mm) 0.058" (1.5 mm) 108-9133
	5.75" (146.0 mm) 0.53" (13.4 mm) 0.66" (16.8 mm) 0.058" (1.5 mm) 108-9134
	6.50" (165.1 mm) 0.28" (7.1 mm) 0.46" (11.7 mm) 0.058" (1.5 mm) 108-9138
	6.50" (165.1 mm) 0.41" (10.3 mm) 0.56" (14.2 mm) 0.058" (1.5 mm) 108-9136
	6.50" (165.1 mm) 0.53" (13.4 mm) 0.66" (16.8 mm) 0.058" (1.5 mm) 108-9137
TITAN HOLLOW EXT. TAPER	HOLLOW EXT. TAPER MAX
	5.75" (146.0 mm) 0.53" (13.4 mm) 0.66" (16.8 mm) 0.058" (1.5 mm) 114-0551
	6.50" (165.1 mm) 0.53" (13.4 mm) 0.66" (16.8 mm) 0.058" (1.5 mm) 114-0550

¾" (19.0 MM) MOUNT – CONTINUED

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN SIDE EJECT					
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9163
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9164
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9165
	6.50" (165.1 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9162
	6.50" (165.1 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9167
	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9168
TITAN SIDE EJECT EXT. TAPER					
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0555
	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0558
TITAN SPLIT					
	5.75" (146.0 mm)	0.51" (12.9 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5122
TITAN FAIRWAY HD					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	108-9260
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	108-9261
TITAN FAIRWAY					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	104-9876
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	104-9875
CLASSIC					
	4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140
	4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670
	5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	0.058" (1.5 mm)	104-0984
	6.50" (165.1 mm)	0.39" (9.9 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	105-1180

TITAN® Max

Part No	Titan Max core ID
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)
108-9176	0.28" (7.1 mm)
108-9178	0.38" (9.7 mm)
108-9180	0.48" (12.2 mm)
108-9166	0.28" (7.1 mm)
108-9182	0.38" (9.7 mm)
108-9184	0.48" (12.2 mm)

Part No	Titan Max core ID
SIDE EJECT EXT. TAPER MAX	
114-0557	0.47" (12.0 mm)
114-0560	0.47" (12.0 mm)


Part No	Titan Max core ID
TITAN SOLID ROUND	
TITAN SOLID SLICING	
TITAN CROSS	

¾" (19.0 MM) MOUNT – CONTINUED

Length	Core dia. (ID)	OD	Wall thickness	Part No	Part No	Titan Max core ID
TITAN SOLID ROUND						
4.50" (114.3 mm)	–	0.25" (6.3 mm)	–	108-9198	–	–
4.50" (114.3 mm)	–	0.30" (7.6 mm)	–	108-9199	–	–
4.50" (114.3 mm)	–	0.35" (8.9 mm)	–	108-9200	–	–
4.50" (114.3 mm)	–	0.40" (10.2 mm)	–	108-9201	–	–
4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9202	–	–
4.50" (114.3 mm)	–	0.60" (15.2 mm)	–	108-9203	–	–
5.50" (139.7 mm)	–	0.25" (6.3 mm)	–	108-9204	–	–
5.50" (139.7 mm)	–	0.30" (7.6 mm)	–	108-9205	–	–
5.50" (139.7 mm)	–	0.35" (8.9 mm)	–	108-9206	–	–
5.50" (139.7 mm)	–	0.40" (10.2 mm)	–	108-9207	–	–
5.50" (139.7 mm)	–	0.50" (12.7 mm)	–	108-9208	–	–
5.50" (139.7 mm)	–	0.60" (15.2 mm)	–	108-9209	–	–
5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9244	–	–
6.50" (165.1 mm)	–	0.30" (7.6 mm)	–	108-9210	–	–
6.50" (165.1 mm)	–	0.35" (8.9 mm)	–	108-9211	–	–
6.50" (165.1 mm)	–	0.40" (10.2 mm)	–	108-9212	–	–
6.50" (165.1 mm)	–	0.50" (12.7 mm)	–	108-9213	–	–
6.50" (165.1 mm)	–	0.60" (15.2 mm)	–	108-9214	–	–
6.50" (165.1 mm)	–	0.75" (19.0 mm)	–	108-9245	–	–
CROSS MAX						
4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9239	–	–
5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9240	–	–
6.50" (165.1 mm)	–	0.75" (19.0 mm)	–	108-9241	–	–
112-1313						
112-1314						

PROCORE® 648/648s

¾" (22.2 MM) MOUNT

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW					
	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9190
	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9191
	5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9192
	5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9193
TITAN SIDE EJECT					
	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9194
	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9195
	5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9196
	5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9197
TITAN SPLIT					
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5121
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.92" (23.4 mm)	0.120" (3.0 mm)	112-5123
CLASSIC					
	4.75" (120.6 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	62-4600
	5.75" (146.0 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	86-9720
TITAN FAIRWAY HD					
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	108-9264
	5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.122" (3.1 mm)	108-9265
TITAN FAIRWAY					
	4.75" (120.6 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7941
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7900
	5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.120" (3.0 mm)	104-9877
TITAN SOLID ROUND					
	5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9246
	5.50" (139.7 mm)	—	0.88" (22.2 mm)	—	108-9247
	6.50" (165.1 mm)	—	0.75" (19.0 mm)	—	108-9248
	6.50" (165.1 mm)	—	0.88" (22.2 mm)	—	108-9249
TITAN SOLID SLICING					
	5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9242
	6.50" (165.1 mm)	—	0.75" (19.0 mm)	—	108-9243
TITAN CROSS					
	5.50" (139.7 mm)	—	0.88" (22.2 mm)	—	108-9259
NEEDLE TINE					
	Length	Core dia. (ID)	OD	Wall thickness	Part No
	6.43" (163.3 mm)	—	5.0 mm	—	100-3620
	7.38" (187.5 mm)	—	8.0 mm	—	100-3621
	5.43" (137.9 mm)	—	5.0 mm	—	125-3319
	Requires needle tine head				
	Requires needle tine head				
	Requires needle tine head				

TITAN® Max

Part No	Titan Max core ID
—	—
—	—
—	—
—	—
SIDE EJECT MAX	
—	—
—	—
108-9188	0.48" (12.2 mm)
—	—

PROCORE® 864/1298



TINE HEADS AND TURF GUARDS

TINE HEADS		TINES REQ'D		TURF GUARDS		TINE HEADS		TINES REQ'D		TURF GUARDS		
Description	Part No	Qty 864	Qty 1298	Part No	Qty 864	Qty 1298	Description	Part No	Qty 864	Qty 1298	Part No	
Quad tine head, 2 rows of 5 ¾" (9.5 mm) mount	09736	80	120	120-1047 120-1052 110-4367 110-4368	2 1 1	4 2 —	Needle tine head	09739	40	60	120-1047 120-1052 110-4367 110-4368	2 1 —
Quad tine head, 1 row of 6 ¾" (9.5 mm) mount	09737	48	72	120-1050 120-1053 115-2801 115-2802	2 1 1	4 2 —	3-tine head ¾" (19.0 mm) mount	09794	24	36	120-1044 110-4358 110-4359 115-4360	2 1 —
4-tine Titan QuickChange ¾" (19.0 mm) or ¾" (22.2 mm) sleeve	09719	32	48	120-1045 120-1046 110-4363 110-4364	2 — 1 1	4 2 — —	4-tine head ¾" (19.0 mm) mount	09796	32	48	120-1045 120-1046 120-1059 120-1060	2 1 —
3-tine Titan QuickChange ¾" (19.0 mm) or ¾" (22.2 mm) sleeve	09711	24	36	120-1044 110-4358 110-4359 110-4360	2 — 1 1	4 2 — —	3-tine head HD ¾" (22.2 mm) mount	09797	24	36	120-1044 110-4358 110-4359 110-4360	2 1 —

5/8" (9.5 MM) MOUNT

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN QUAD					
	4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	108-9104
	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	108-9105
	4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9106
	4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	108-9293
	5.00" (127.0 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	138-5937
	5.00" (127.0 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	137-6526
	5.00" (127.0 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	137-6527
	5.00" (127.0 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	137-6529
	5.50" (139.7 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9290
TITAN SOLID ROUND					
	4.50" (114.3 mm)	—	0.20" (5.1 mm)	—	108-9230
	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9231
	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9232
	4.50" (114.3 mm)	—	0.38" (9.7 mm)	—	108-9233
	5.50" (139.7 mm)	—	0.20" (5.1 mm)	—	108-9234
	5.50" (139.7 mm)	—	0.25" (6.3 mm)	—	108-9235
	5.50" (139.7 mm)	—	0.30" (7.6 mm)	—	108-9236
	5.50" (139.7 mm)	—	0.38" (9.7 mm)	—	108-9237
TITAN SOLID SLICING					
	5.00" (127.0 mm)	—	0.63" (15.9 mm)	—	108-9238
TITAN CROSS					
	4.50" (114.3 mm)	—	0.38" (9.5 mm)	—	108-9215
	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9216
	4.50" (114.3 mm)	—	0.62" (15.7 mm)	—	108-9217
	5.50" (139.7 mm)	—	0.38" (9.5 mm)	—	108-9218
	5.50" (139.7 mm)	—	0.50" (12.7 mm)	—	108-9219
	5.50" (139.7 mm)	—	0.62" (15.7 mm)	—	108-9220

3/4" (19.0 MM) MOUNT

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW					
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9128
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9129
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9130
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9132
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9133
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9134
	6.50" (165.1 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9138
	6.50" (165.1 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9136
	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9137

TITAN® Max

Part No	Titan Max core ID
QUAD MAX	
108-9112	0.23" (5.8 mm)
108-9114	0.28" (7.1 mm)
108-9116	0.38" (9.7 mm)
—	—
108-9120	0.23" (5.8 mm)
108-9122	0.28" (7.1 mm)
108-9124	0.38" (9.7 mm)
—	—
—	—
CROSS MAX	
—	—
112-1310	—
—	—
—	—
112-1311	—
—	—
TITAN® Max	
Part No	Titan Max core ID

3/4" (19.0 MM) MOUNT – CONTINUED

Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW EXT. TAPER				
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0551
6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0550
SIDE EJECT				
4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159
4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160
4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161
5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9163
5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9164
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9165
6.50" (165.1 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9162
6.50" (165.1 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9167
6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9168
TITAN SIDE EJECT EXT. TAPER				
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0555
6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0558
TITAN SPLIT				
5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5122
—	—	—	—	—
TITAN FAIRWAY HD				
5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	108-9260
5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	108-9261
TITAN FAIRWAY				
5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.1 mm)	104-9876
5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	104-9875
CLASSIC				
4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140
4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670
5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	0.058" (1.5 mm)	104-0984
6.50" (165.1 mm)	0.39" (9.9 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	105-1180
—	—	—	—	—
—	—	—	—	—
—	—	—	—	—
—	—	—	—	—

TITAN® Max

Part No	Titan Max core ID
HOLLOW EXT. TAPER MAX	
114-0553	0.47" (12.0 mm)
—	—
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)
108-9176	0.28" (7.1 mm)
108-9	

PROCORE® 440/660/880



TINE HEADS AND TURF GUARDS

TINE HEADS		TINES REQ'D		TURF GUARDS					
Description	Part No	Qty 660	Qty 880	Part No	Qty 660	Qty 880	Part No	Qty 660	Qty 880
Needle tine head 660/880	09720	48	64	100-5418	6	—	100-5415	1	—
				100-5419	—	7			
Quad tine head, $\frac{3}{8}$ " (9.5 mm) mount	09721	60	80	100-5420	1	5	100-5421	8	4
3-tine head, $\frac{3}{8}$ " (19.0 mm) mount	09722	18	24	100-5414	2	5	100-5415	3	—
4-tine head, $\frac{3}{8}$ " (19.0 mm) mount	09723	24	32	100-5416	5	1	100-5417	—	4
3-tine head, $\frac{7}{8}$ " (22.2 mm) mount	09733	18	24	100-5414	2	5	100-5415	3	—
4-tine head, $\frac{7}{8}$ " (22.2 mm) mount	09734	24	32	100-5416	5	1	100-5417	—	4



$\frac{3}{8}$ " (9.5 MM) MOUNT

TITAN QUAD	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	108-9104
	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	108-9105
	4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9106
	4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	108-9293
	5.00" (127.0 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	138-5937
	5.00" (127.0 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	137-6526
	5.00" (127.0 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	137-6527
	5.00" (127.0 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	137-6529
	5.50" (139.7 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9290
TITAN SOLID ROUND	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.50" (114.3 mm)	—	0.20" (5.1 mm)	—	108-9230
	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9231
	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9232
	4.50" (114.3 mm)	—	0.38" (9.7 mm)	—	108-9233
	5.50" (139.7 mm)	—	0.20" (5.1 mm)	—	108-9234
	5.50" (139.7 mm)	—	0.25" (6.3 mm)	—	108-9235
	5.50" (139.7 mm)	—	0.30" (7.6 mm)	—	108-9236
	5.50" (139.7 mm)	—	0.38" (9.7 mm)	—	108-9237
TITAN SOLID SLICING	Length	Core dia. (ID)	OD	Wall thickness	Part No
	5.00" (127.0 mm)	—	0.63" (15.9 mm)	—	108-9238
TITAN CROSS	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.50" (114.3 mm)	—	0.38" (9.5 mm)	—	108-9215
	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9216
	4.50" (114.3 mm)	—	0.62" (15.7 mm)	—	108-9217
	5.50" (139.7 mm)	—	0.38" (9.5 mm)	—	108-9218
	5.50" (139.7 mm)	—	0.50" (12.7 mm)	—	108-9219
	5.50" (139.7 mm)	—	0.62" (15.7 mm)	—	108-9220
$\frac{3}{4}$ " (19.0 MM) MOUNT	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9128
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9129
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9130
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9132
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9133
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9134

TITAN® Max

Part No	Titan Max core ID
QUAD MAX	
108-9112	0.23" (5.8 mm)
108-9114	0.28" (7.1 mm)
108-9116	0.38" (9.7 mm)
—	—
108-9120	0.23" (5.8 mm)
108-9122	0.28" (7.1 mm)
108-9124	0.38" (9.7 mm)
—	—
—	—
CROSS MAX	
—	—
—	—
—	—
—	—
112-1310	—
—	—
—	—
112-1311	—
—	—
TITAN® Max	
Part No	Titan Max core ID
HOLLOW MAX	
108-9139	0.28" (7.1 mm)
108-9141	0.38" (9.7 mm)
108-9143	0.48" (12.2 mm)
—	—
108-9147	0.38" (9.7 mm)
108-9149	0.48" (12.2 mm)

¾" (19.0 MM) MOUNT – CONTINUED

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW EXT. TAPER					
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0551
TITAN SIDE EJECT					
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9163
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9164
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9165
TITAN SIDE EJECT EXT. TAPER MAX					
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0555
TITAN SPLIT					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5122
TITAN FAIRWAY HD					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	108-9260
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	108-9261
TITAN FAIRWAY					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	104-9876
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	104-9875
CLASSIC					
	4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140
	4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670
	5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	0.058" (1.5 mm)	104-0984
TITAN SOLID ROUND					
	4.50" (114.3 mm)	–	0.25" (6.3 mm)	–	108-9198
	4.50" (114.3 mm)	–	0.30" (7.6 mm)	–	108-9199
	4.50" (114.3 mm)	–	0.35" (8.9 mm)	–	108-9200
	4.50" (114.3 mm)	–	0.40" (10.2 mm)	–	108-9201
	4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9202
	4.50" (114.3 mm)	–	0.60" (15.2 mm)	–	108-9203
	5.50" (139.7 mm)	–	0.25" (6.3 mm)	–	108-9204
	5.50" (139.7 mm)	–	0.30" (7.6 mm)	–	108-9205
	5.50" (139.7 mm)	–	0.35" (8.9 mm)	–	108-9206
	5.50" (139.7 mm)	–	0.40" (10.2 mm)	–	108-9207
	5.50" (139.7 mm)	–	0.50" (12.7 mm)	–	108-9208
	5.50" (139.7 mm)	–	0.60" (15.2 mm)	–	108-9209
	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9244
TITAN SOLID SLICING					
	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9239
	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9240

TITAN® Max

Part No	Titan Max core ID
HOLLOW EXT. TAPER MAX	
114-0553	0.47" (12.0 mm)
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)
108-9176	0.28" (7.1 mm)
108-9178	0.38" (9.7 mm)
108-9180	0.48" (12.2 mm)

¾" (19.0 MM) MOUNT – CONTINUED

Length	Core Dia. (ID)	OD	Wall Thickness	Part Number
TITAN CROSS				
4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9221
4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9223
5.50" (139.7 mm)	–	0.50" (12.7 mm)	–	108-9224
5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9226

⅝" (22.2 MM) MOUNT

Length	Core Dia. (ID)	OD	Wall Thickness	Part Number
TITAN HOLLOW				
4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9190
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9191
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9192
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9193

TITAN SIDE EJECT

4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9194
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9195
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9196
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9197

TITAN SPLIT

5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5121
5.75" (146.0 mm)	0.64" (16.1 mm)	0.92" (23.4 mm)	0.120" (3.0 mm)	112-5123

TITAN FAIRWAY HD

5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	108-9264
5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.122" (3.1 mm)	108-9265

TITAN FAIRWAY

4.75" (120.6 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7941
5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7900
5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.120" (3.0 mm)	104-9877

CLASSIC

GREENS AERATOR

GREENS AERATOR



TINE HEADS AND TURF GUARDS



TINE HEADS		TINES REQ'D	TURF GUARDS	
Description	Part No		Part No	Qty Req'd
3/8" (9.5 mm) needle tine head	94-3421 Outboard block 94-6822 Inboard block	12		
1/2" (12.7 mm) tine head	94-3420	12	72-4660 (RH) 72-4680 (Ctr) 72-4640 (LH)	1
3/4" (19.0 mm) tine head	59-2500	12		
7/8" (22.2 mm) tine head	62-4610	12		

3/8" (9.5 MM) MOUNT

TITAN QUAD	Length	Core dia. (ID)	OD	Wall thickness	Part No
	4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	108-9104
	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	108-9105
	4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9106
	4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	108-9293

TITAN SOLID ROUND

TITAN SOLID ROUND	Length	Core dia.	OD	Wall thickness	Part No
	4.50" (114.3 mm)	—	0.20" (5.1 mm)	—	108-9230
	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9231
	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9232
	4.50" (114.3 mm)	—	0.38" (9.7 mm)	—	108-9233

TITAN CROSS

TITAN CROSS	Length	Core Dia.	OD	Wall Thickness	Part Number
	4.50" (114.3 mm)	—	0.38" (9.5 mm)	—	108-9215
	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9216
	4.50" (114.3 mm)	—	0.63" (15.9 mm)	—	108-9217

3/4" (19.0 MM) MOUNT

TITAN HOLLOW	Length	Core Dia. (ID)	OD	Wall Thickness	Part Number
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9128
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9129
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9130

TITAN SIDE EJECT

TITAN SIDE EJECT	Length	Core Dia.	OD	Wall thickness	Part Number
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161

CLASSIC

CLASSIC	Length	Core Dia.	OD	Wall thickness	Part Number
	4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140
	4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670

TITAN SOLID ROUND

TITAN SOLID ROUND	Length	Core dia.	OD	Wall thickness	Part No
	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9198
	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9199
	4.50" (114.3 mm)	—	0.35" (8.9 mm)	—	108-9200
	4.50" (114.3 mm)	—	0.40" (10.2 mm)	—	108-9201
	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9202
	4.50" (114.3 mm)	—	0.60" (15.2 mm)	—	108-9203

TITAN® Max

Part No	Titan Max Core ID
QUAD MAX	
108-9112	0.23" (5.8 mm)
108-9114	0.28" (7.1 mm)
108-9116	0.38" (9.7 mm)
—	—
CROSS MAX	
—	—
—	—
—	—
—	—
—	—
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)

TITAN® Max

Part Number	Titan Max Core ID
HOLLOW MAX	
108-9139	0.28" (7.1 mm)
108-9141	0.38" (9.7 mm)
108-9143	0.48" (12.2 mm)
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)

GREENS AERATOR

¾" (19.0 MM) MOUNT – CONTINUED

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN SOLID SLICING					
	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9239
TITAN CROSS					
	4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9221
	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9223
⅜" (22.2 MM) MOUNT					
	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW					
	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9190
	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9191
TITAN SIDE EJECT					
	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9194
	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9195
CLASSIC					
	4.75" (120.6 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	62-4600
TITAN FAIRWAY					
	4.75" (120.6 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7941

NEEDLE TINE

	Length	Core Dia. (ID)	OD	Wall Thickness	Part Number
	6.43" (163.3 mm)	–	5.0 mm	–	100-3620

FAIRWAY AERATOR






TINE HEADS AND TURF GUARDS

TINE HEADS		TINES REQ'D	TURF GUARDS	
Description	Part No		Part No	Qty Req'd
6-tine, ¾" (19.0 mm) Block	Outer	95-3103	36	70-9430
	Bridging	95-3104		
	Inner	95-3105		
6-tine, ⅜" (22.2 mm) Block	Outer	70-9380	12	70-9440
	Bridging	70-9390		
	Inner	70-9400		

FAIRWAY AERATOR

FAIRWAY AERATOR

¾" (19.0 MM) MOUNT

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW					
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9128
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9129
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9130
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9132
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9133
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9134
TITAN HOLLOW EXT. TAPER					
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0551
TITAN SIDE EJECT					
	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159
	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160
	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161
	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9163
	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9164
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9165
TITAN SIDE EJECT EXT. TAPER					
	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0555
TITAN SPLIT					
	5.75" (146.0 mm)	0.64" (16.26 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5122
					—
TITAN FAIRWAY HD					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	108-9260
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	108-9261
TITAN FAIRWAY					
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	104-9876
	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	104-9875
CLASSIC					
	4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140
	4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670
	5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	0.058" (1.5 mm)	104-0984

TITAN® Max

Part No	Titan Max core ID
HOLLOW MAX	
108-9139	0.28" (7.1 mm)
108-9141	0.38" (9.7 mm)
108-9143	0.48" (12.2 mm)
—	—
108-9147	0.38" (9.7 mm)
108-9149	0.48" (12.2 mm)
HOLLOW EXT. TAPER MAX	
114-0553	0.47" (12.0 mm)
SIDE EJECT MAX	
108-9170	0.28" (7.1 mm)
108-9172	0.38" (9.7 mm)
108-9174	0.48" (12.2 mm)
108-9176	0.28" (7.1 mm)
108-9178	0.38" (9.7 mm)
108-9180	0.48" (12.2 mm)
SIDE EJECT EXT. TAPER MAX	
114-0557	0.47" (12.0 mm)

¾" (19.0 MM) MOUNT – CONTINUED

Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN SOLID ROUND				
4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9198
4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9199
4.50" (114.3 mm)	—	0.35" (8.9 mm)	—	108-9200
4.50" (114.3 mm)	—	0.40" (10.2 mm)	—	108-9201
4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9202
4.50" (114.3 mm)	—	0.60" (15.2 mm)	—	108-9203
5.50" (139.7 mm)	—	0.25" (6.3 mm)	—	108-9204
5.50" (139.7 mm)	—	0.30" (7.6 mm)	—	108-9205
5.50" (139.7 mm)	—	0.35" (8.9 mm)	—	108-9206
5.50" (139.7 mm)	—	0.40" (10.2 mm)	—	108-9207
5.50" (139.7 mm)	—	0.50" (12.7 mm)	—	108-9208
5.50" (139.7 mm)	—	0.60" (15.2 mm)	—	108-9209
5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9244
TITAN CROSS				
4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9221
4.50" (114.3 mm)	—	0.75" (19.0 mm)	—	108-9223
5.50" (139.7 mm)	—	0.50" (12.7 mm)	—	108-9224
5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9226

TITAN® Max

Part No	Titan Max Core ID
CROSS MAX	
—	—
—	—
112-1313	—
—	—

⅝" (22.2 MM) MOUNT

Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN HOLLOW				
4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9190
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9191
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9192
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9193
TITAN SIDE EJECT				
4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9194
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9195
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9196
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9197
TITAN SPLIT				
5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5121
5.75" (146.0 mm)	0.64" (16.1 mm)	0.92" (23.4 mm)	0.120" (3.0 mm)	112-5123

TITAN® Max

Part No	Titan Max core ID
HOLLOW MAX	
—	—
—	—
108-9157	0.48" (12.2 mm)
—	

FAIRWAY AERATOR

7/8" (22.2 MM) MOUNT – CONTINUED

	Length	Core dia. (ID)	OD	Wall thickness	Part No
TITAN FAIRWAY HD					
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	108-9264
	5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.122" (3.1 mm)	108-9265
TITAN FAIRWAY					
	4.75" (120.6 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7941
	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7900
	5.75" (146.0 mm)	0.64" (16.1 mm)	1.00" (25.4 mm)	0.120" (3.0 mm)	104-9877
CLASSIC					
	4.75" (120.6 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	62-4600
	5.75" (146.0 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	86-9720
TITAN SOLID ROUND					
	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9246
	5.50" (139.7 mm)	–	0.88" (22.2 mm)	–	108-9247
TITAN SOLID SLICING					
	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9239
	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9240
	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9242
TITAN CROSS					
	5.50" (139.7 mm)	–	0.88" (22.2 mm)	–	108-9259

TURF AERATOR 686/687



TURF AERATOR 686/687

	Part No	Size	Quantity required
SPOON-OPEN			
	108-9296	1/2" (12.7 mm)	96 tines
	108-9298	3/4" (19.0 mm)	96 tines
SPOON-CLOSED			
	108-9297	1/2" (12.7 mm)	96 tines
	108-9299	3/4" (19.0 mm)	96 tines

PROCORE® SR SERIES



The ProCore SR series provides working widths of 48"-75" (122–190 cm), working depths up to 16" (40.6 cm) and hole spacing from 2.5"-6" (6.3–15.2 cm).

5/16" (7.9 MM), 12 MM OR 18 MM MOUNT

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8614	—	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8615	—	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8624	—	SGT10750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.81" (20.6 mm)	139-8613	—	SGT10813H
18.0 mm	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8622	—	SGT08125
18.0 mm	8.00" (203.2 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8628	—	SGT08100H
18.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8623	—	SGT10750
18.0 mm	10.00" (254.0 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8617	—	139-8617
18.0 mm	10.00" (254.0 mm)	0.76" (19.3 mm)	1.00" (25.4 mm)	139-8619	—	SGT10100S
18.0 mm	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8623	—	SGT12125
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.31" (7.9 mm)	SGS07313*	SGA08313	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.31" (7.9 mm)	SGS08313*	SGA08313	—
3/8" (9.5 mm)	9.00" (228.6 mm)	—	0.38" (9.5 mm)	SGS08375*	SGA12375	—
3/8" (9.5 mm)	10.75" (273.1 mm)	—	0.38" (9.5 mm)	SGS10374*	SGA12375	—
3/8" (9.5 mm)	12.25" (311.2 mm)	—	0.38" (9.5 mm)	SGS10375*	SGA12375	—
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	10.75" (273.1 mm)	—	12.0 mm	SGS10504	—	—
12.0 mm	12.25" (311.2 mm)	—	12.0 mm	SGS10500	—	—
12.0 mm	14.25" (361.9 mm)	—	12.0 mm	SGS12500	—	—
12.0 mm	16.25" (412.8 mm)	—	12.0 mm	SGS14500	—	—
18.0 mm	12.25" (311.2 mm)	—	18.0 mm	SGS10750	—	—
18.0 mm	12.50" (317.5 mm)	—	18.0 mm	SGS10875	—	—
18.0 mm	14.00" (355.6 mm)	—	18.0 mm	SGS12875	—	—
18.0 mm	14.25" (361.9 mm)	—	18.0 mm	SGS12750	—	—
18.0 mm	16.00" (406.4 mm)	—	18.0 mm	SGS14875	—	—
18.0 mm	16.25" (412.8 mm)	—	18.0 mm	SGS14750	—	—

SR48 ADAPTER HEAD KIT 117-7190

SOLID TINES
5/16" (7.9 mm) 8.50" (215.9 mm) — 0.31" (7.9 mm) SGS07313 — —
5/16" (7.9 mm) 10.00" (254.0 mm) — 0.31" (7.9 mm) SGS08313 — —

SR48 ADAPTER HEAD KIT 117-7191

CORING TINES
12.0 mm 7.00" (177.8 mm) 0.52" (13.2 mm) 0.69" (17.4 mm) 139-8616 — SGT07625
12.0 mm 7.00" (177.8 mm) 0.56" (14.2 mm) 0.81" (20.7 mm) 139-8625 — SGT07750
12.0 mm 10.00" (254.0 mm) 0.56" (14.2 mm) 0.75" (19.0 mm) 139-8620 — SGT10750

SOLID TINES
12.0 mm 8.00" (203.2 mm) — 12.0 mm SGS08500 — —
12.0 mm 12.25" (311.2 mm) — 12.0 mm SGS10500 — —
12.0 mm 14.25" (361.9 mm) — 12.0 mm SGS12500 — —
12.0 mm 16.25" (412.8 mm) — 12.0 mm SGS14500 — —

PROCORE® SR SERIES SR54

PROCORE® SR SERIES SR54-S

5/16" (7.9 MM) OR 12 MM MOUNT

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	SGA10375	-
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	-	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	-	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	-	SGT10750
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	-	0.31" (7.9 mm)	SGS07313	-	-
5/16" (7.9 mm)	10.00" (254.0 mm)	-	0.31" (7.9 mm)	SGS08313	-	-
5/16" (9.5 mm)	9.00" (228.6 mm)	-	0.38" (9.5 mm)	SGS08375*	SGA10375	-
5/16" (9.5 mm)	10.75" (273.1 mm)	-	0.38" (9.5 mm)	SGS10374*	SGA10375	-
12.0 mm	8.00" (203.2 mm)	-	12.0 mm	SGS08500	-	-
12.0 mm	10.75" (273.1 mm)	-	12.0 mm	SGS10504	-	-

SR 54 ADAPTER HEAD KIT 117-7193 (36 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	-	SGT05550
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	-	0.31" (7.9 mm)	SGS07313	-	-
5/16" (7.9 mm)	10.00" (254.0 mm)	-	0.31" (7.9 mm)	SGS08313	-	-
5/16" (9.5 mm)	9.00" (228.6 mm)	-	0.38" (9.5 mm)	SGS08375*	SGA10375	-
5/16" (9.5 mm)	10.75" (273.1 mm)	-	0.38" (9.5 mm)	SGS10374*	SGA10375	-
5/16" (9.5 mm)	12.25" (311.2 mm)	-	0.38" (9.5 mm)	SGS10375*	SGA10375	-

*Longer shank tine.

SR 54 ADAPTER HEAD KIT 117-7193 (36 TINES) – CONTINUED

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	-	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	-	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	-	SGT10750
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	-	0.31" (7.9 mm)	SGS07313	-	-
5/16" (7.9 mm)	10.00" (254.0 mm)	-	0.31" (7.9 mm)	SGS08313	-	-
12.0 mm	8.00" (203.2 mm)	-	12.0 mm	SGS08500	-	-
12.0 mm	10.75" (273.1 mm)	-	12.0 mm	SGS10504	-	-

SR 54-S ADAPTER HEAD KIT 117-7194 (12 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
18.0 mm	12.25" (311.2 mm)	-	18.0 mm	SGS10750	-	-

SR 54-S ADAPTER HEAD KIT 117-7195 (12 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	-	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	-	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	-	SGT10750
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	-	0.31" (7.9 mm)	SGS07313	-	-
5/16" (7.9 mm)	10.00" (254.0 mm)	-	0.31" (7.9 mm)	SGS08313	-	-
12.0 mm	8.00" (203.2 mm)	-	12.0 mm	SGS08500	-	-
12.0 mm	10.75" (273.1 mm)	-	12.0 mm	SGS10504	-	-

SR 54-S ADAPTER HEAD KIT 117-7196 (24 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	-	SGT05550
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	-	0.31" (7.9 mm)	SGS07313	-	-
5/16" (7.9 mm)	10.00" (254.0 mm)	-	0.31" (7.9 mm)	SGS08313	-	-
5/16" (9.5 mm)	9.00" (228.6 mm)	-	0.38" (9.5 mm)	SGS08375	-	-
5/16" (9.5 mm)	10.75" (273.1 mm)	-	0.38" (9.5 mm)	SGS10374	-	-

SR 54-S ADAPTER HEAD KIT 117-7199 (48 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	-	SGT05550
SOLID TINES						
5/16" (9.5 mm)	9.00" (228.6 mm)	-	0.38" (9.5 mm)	SGS08375	-	-
5/16" (9.5 mm)	10.75" (273.1 mm)	-	0.38" (9.5 mm)	SGS10374	-	-

PROCORE® SR SERIES SR70

PROCORE® SR SERIES SR70-S

5/16" (7.9 MM) OR 12 MM MOUNT

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	SGA10375	SGT05550
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	—	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	—	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	—	SGT10750
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.31" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.31" (7.9 mm)	SGS08313	—	—
5/16" (9.5 mm)	9.00" (228.6 mm)	—	0.38" (9.5 mm)	SGS08375	SGA10375	—
5/16" (9.5 mm)	10.75" (273.1 mm)	—	0.38" (9.5 mm)	SGS10374	SGA10375	—
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	10.75" (273.1 mm)	—	12.0 mm	SGS10504	—	—

SR70 ADAPTER HEAD KIT 117-7193 (48 TINES)

Mount	Length	Core Dia. (ID)	OD	Part	Adapter Sleeve	Replacement Tube
CORING TINES						
5/16" (9.5 mm)	5.50" (139.7 mm)	—	0.50" (12.7 mm)	139-8618	—	5/16" (9.5 mm)
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.3125" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.3125" (7.9 mm)	SGS08313	—	—
5/16" (9.5 mm)	9.00" (228.6 mm)	—	0.375" (9.5 mm)	SGS08375	—	—
5/16" (9.5 mm)	10.75" (273.1 mm)	—	0.375" (9.5 mm)	SGS10374	—	—
5/16" (9.5 mm)	12.25" (311.2 mm)	—	0.375" (9.5 mm)	SGS10375	—	—

SR70 ADAPTER HEAD KIT 117-7193 (48 TINES)

Mount	Length	Core Dia. (ID)	OD	Part	Adapter Sleeve	Replacement Tube
CORING TINES						
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	—	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	—	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	—	SGT10750
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.3125" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.3125" (7.9 mm)	SGS08313	—	—
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	10.75" (273.1 mm)	—	12.0 mm	SGS10504	—	—

SR70-S ADAPTER HEAD KIT 117-7194 (16 TINES)

SOLID TINES	18.0 mm	12.25" (311.2 mm)	—	18.0 mm	SGS10750	—	—
-------------	---------	-------------------	---	---------	----------	---	---

SR70-S ADAPTER HEAD KIT 117-7195 (16 TINES)

CORING TINES	12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	—	SGT07625
SOLID TINES	12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	—	SGT07750
SOLID TINES	12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	—	SGT10750

SOLID TINES

5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.3125" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.3125" (7.9 mm)	SGS08313	—	—
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	10.75" (273.1 mm)	—	12.0 mm	SGS10504	—	—

SR70-S ADAPTER HEAD KIT 117-7196 (32 TINES)

CORING TINES	5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	—	SGT05550
--------------	----------------	------------------	----------------	-----------------	----------	---	----------

SOLID TINES

5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.3125" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.3125" (7.9 mm)	SGS08313	—	—
5/16" (9.5 mm)	9.00" (228.6 mm)	—	0.375" (9.5 mm)	SGS08375	—	—
5/16" (9.5 mm)	10.75" (273.1 mm)	—	0.375" (9.5 mm)	SGS10374	—	—

SR70-S ADAPTER HEAD KIT 117-7199 (64 TINES)

CORING TINES	5/16" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	139-8618	—	SGT05550
--------------	----------------	------------------	----------------	-----------------	----------	---	----------

SOLID TINES

5/16" (9.5 mm)	9.00" (228.6 mm)	—	0.375" (9.5 mm)	SGS08375	—	—
5/16" (9.5 mm)	10.75" (273.1 mm)	—	0.375" (9.5 mm)	SGS10374	—	—

PROCORE® SR SERIES SR72
PROCORE® SR SERIES SR75
5/16" (7.9 MM), 12 MM OR 18 MM MOUNT

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
CORING TINES						
12.0 mm Long	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8614	—	SGT07625
12.0 mm Long	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8615	—	SGT07750
12.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8624	—	SGT10750
12.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.81" (20.6 mm)	139-8613	—	SGT10813H
18.0 mm Long	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8622	—	SGT10750
18.0 mm Long	8.00" (203.2 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8628	—	SGT08100H
18.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8623	—	SGT10100S
18.0 mm Long	10.00" (254.0 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8617	—	139-8617
18.0 mm Long	10.00" (254.0 mm)	0.76" (19.3 mm)	1.00" (25.4 mm)	139-8619	—	SGT08125
18.0 mm Long	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8627	—	SGT12125
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.31" (7.9 mm)	SGS07313	SGA08313	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.31" (7.9 mm)	SGS08313	SGA08313	—
3/8" (9.5 mm)	9.00" (228.6 mm)	—	0.375" (9.5 mm)	SGS08375	SGA12375	—
3/8" (9.5 mm)	10.75" (273.1 mm)	—	0.375" (9.5 mm)	SGS10374	SGA12375	—
3/8" (9.5 mm)	12.25" (311.2 mm)	—	0.375" (9.5 mm)	SGS10375	SGA12375	—
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	10.75" (273.1 mm)	—	12.0 mm	SGS10504	—	—
12.0 mm	12.25" (311.2 mm)	—	12.0 mm	SGS10500	—	—
12.0 mm	14.25" (361.9 mm)	—	12.0 mm	SGS12500	—	—
12.0 mm	16.25" (412.8 mm)	—	12.0 mm	SGS14500	—	—
18.0 mm	12.25" (311.2 mm)	—	18.0 mm	SGS10750	—	—
18.0 mm	12.50" (317.5 mm)	—	18.0 mm	SGS10875	—	—
18.0 mm	14.00" (355.6 mm)	—	18.0 mm	SGS12875	—	—
18.0 mm	14.25" (361.9 mm)	—	18.0 mm	SGS12750	—	—
18.0 mm	16.00" (406.4 mm)	—	18.0 mm	SGS14875	—	—
18.0 mm	16.25" (412.8 mm)	—	18.0 mm	SGS14750	—	—
SR72 ADAPTER HEAD KIT 117-7190 (60 TINES)						
SOLID TINES						
5/16" (7.9 mm)	8.50" (215.9 mm)	—	0.3125" (7.9 mm)	SGS07313	—	—
5/16" (7.9 mm)	10.00" (254.0 mm)	—	0.3125" (7.9 mm)	SGS08313	—	—

SR72 ADAPTER HEAD KIT 117-7191 (60 TINES)

Coring Tines						
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8616	—	SGT07625
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8625	—	SGT07750
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8620	—	SGT10750
Solid Tines						
12.0 mm	8.00" (203.2 mm)	—	12.0 mm	SGS08500	—	—
12.0 mm	12.25" (311.2 mm)	—	12.0 mm	SGS10500	—	—
12.0 mm	14.25" (361.9 mm)	—	12.0 mm	SGS12500	—	—
12.0 mm	16.25" (412.8 mm)	—	12.0 mm	SGS14500	—	—

5/8" (22.2 MM) MOUNT

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
Coring Tines						
18.0 mm Long	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8622	SG715802	SGT08125
18.0 mm Long	8.00" (203.2 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8628	SG715802	SGT08100H
18.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8623	SG715802	SGT10750
18.0 mm Long	10.00" (254.0 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8617	SG715802	139-8617
18.0 mm Long	10.00" (254.0 mm)	0.76" (19.3 mm)	1.00" (25.4 mm)	139-8619	SG715802	SGT10100S
18.0 mm Long	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8627	SG715802	SGT12125
18.0 mm Long	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8626	—	SGT08125
18.0 mm Long	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8621	—	SGT12125
Solid Tines						
18.0 mm	12.25" (311.2 mm)	—	18.0 mm	SGS10750	SG715802	—
18.0 mm	12.50" (317.5 mm)	—	18.0 mm	SGS10875	SG715802	—
18.0 mm	14.00" (355.6 mm)	—	18.0 mm	SGS12875	SG715802	—
18.0 mm	14.25" (361.9 mm)	—	18.0 mm	SGS12750	SG715802	—
18.0 mm	16.00" (406.4 mm)	—	18.0 mm	SGS14875	SG715802	—
18.0 mm	16.25" (412.8 mm)	—	18.0 mm	SGS14750	SG715802	—

SR75 ADAPTER HEAD KIT 117-7198 (5/32X15/32" [4X12 MM] = 24 TINES OR 1/8X11/16" [3X18MM] = 18 TINES)

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	Replacement tube
Coring Tines						
12.0 mm Long	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	139-8614	—	SGT07625
12.0 mm Long	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	139-8615	—	SGT07750
12.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.81" (20.6 mm)	139-8613	—	SGT10813H
12.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8624	—	SGT10750
18.0 mm Long	8.00" (203.2 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	139-8628	—	SGT08100H
18.0 mm Long	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8622	—	SGT08125
18.0 mm Long	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	139-8623	—	SGT07625
18.0 mm Long	10.00" (254.0 mm)	0.76" (19.3 mm)	1.00" (25.4 mm)	139-8619	—	SGT10100S
18.0 mm Long	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	139-8627	—	SGT12125

*Longer shank tine.

*Longer shank tine.

PROCORE® SR SERIES SR75

ADAPTER HEAD KIT 117-7198 – CONTINUED

Mount	Length	Core dia. (ID)	OD	Part	Adapter sleeve	12.0 mm Replacement tube
SOLID TINES						
12.0 mm	8.00" (203.2 mm)	–	12.0 mm	SGS08500	–	–
12.0 mm	10.75" (273.1 mm)	–	12.0 mm	SGS10504	–	–
12.0 mm	12.25" (311.2 mm)	–	12.0 mm	SGS10500	–	–
12.0 mm	14.25" (361.9 mm)	–	12.0 mm	SGS12500	–	–
12.0 mm	16.25" (412.8 mm)	–	12.0 mm	SGS14500	–	–
18.0 mm	12.25" (311.2 mm)	–	18.0 mm	SGS10750	–	–
18.0 mm	12.50" (317.5 mm)	–	0.875" (22.2 mm)	SGS10875	–	–
18.0 mm	14.00" (355.6 mm)	–	0.875" (22.2 mm)	SGS12875	–	–
18.0 mm	14.25" (361.9 mm)	–	18.0 mm	SGS12750	–	–
18.0 mm	16.00" (406.4 mm)	–	0.875" (22.2 mm)	SGS14875	–	–
18.0 mm	16.25" (412.8 mm)	–	18.0 mm	SGS14750	–	–

COMPETITIVE MODELS



TITAN® conversion sleeves

Part No	Description	Mount
112-1300	Sleeve	½" (12.7 mm)
112-1301	Sleeve	⅝" (15.9 mm)

Easily converts TITAN® tines to ½" (12.7 mm) and ⅝" (15.9 mm) mount. Toro® conversion sleeves allow the complete selection of Toro tines to fit on most competitive equipment. The conversion sleeve slides onto a ⅝" (9.5 mm) mount Toro tine to create a ½" (12.7 mm) mount or ⅝" (15.9 mm) mount.

TITAN® TINES COMPETITIVE MODELS

3/8" (9.5 MM) MOUNT					TITAN® Max		Competitive model	
Length	Core dia. (ID)	OD	Part No	Wall	Part No	Core dia. (ID)	Ryan® GA 24/30/60	John Deere®
TITAN QUAD								
4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	108-9104	0.052" (1.3 mm)	108-9112	0.23" (5.8 mm)	X	X
4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	108-9105	0.063" (1.6 mm)	108-9114	0.28" (7.1 mm)	X	X
4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	108-9106	0.063" (1.6 mm)	108-9116	0.38" (9.7 mm)	X	X
4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	108-9293	0.049" (1.2 mm)	-	-	X	X
5.00" (127.0 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	138-5937	0.052" (1.3 mm)	108-9120	0.23" (5.8 mm)	X	X
5.00" (127.0 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	137-6526	0.063" (1.6 mm)	108-9122	0.28" (7.1 mm)	X	X
5.00" (127.0 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	137-6527	0.063" (1.6 mm)	108-9124	0.38" (9.7 mm)	X	X
5.00" (127.0 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	137-6529	0.049" (1.2 mm)			X	X
TITAN SOLID ROUND								
4.50" (114.3 mm)	-	0.20" (5.1 mm)	108-9230	-	-	-	X	X
4.50" (114.3 mm)	-	0.25" (6.3 mm)	108-9231	-	-	-	X	X
4.50" (114.3 mm)	-	0.30" (7.6 mm)	108-9232	-	-	-	X	X
4.50" (114.3 mm)	-	0.38" (9.7 mm)	108-9233	-	-	-	X	X
5.50" (139.7 mm)	-	0.20" (5.1 mm)	108-9234	-	-	-	X	X
5.50" (139.7 mm)	-	0.25" (6.3 mm)	108-9235	-	-	-	X	X
5.50" (139.7 mm)	-	0.30" (7.6 mm)	108-9236	-	-	-	X	X
5.50" (139.7 mm)	-	0.38" (9.7 mm)	108-9237	-	-	-	X	X
TITAN SOLID SLICING								
5.00" (127.0 mm)	-	0.63" (15.9 mm)	108-9238	-	-	-	X	X
TITAN CROSS								
4.50" (114.3 mm)	-	0.38" (9.5 mm)	108-9215	-	-	-	X	X
4.50" (114.3 mm)	-	0.50" (12.7 mm)	108-9216	-	112-1310	-	X	X
4.50" (114.3 mm)	-	0.63" (15.9 mm)	108-9217	-	-	-	X	X
5.50" (139.7 mm)	-	0.38" (9.5 mm)	108-9218	-	-	-	X*	X
5.50" (139.7 mm)	-	0.50" (12.7 mm)	108-9219	-	112-1311	-	X*	X
5.50" (139.7 mm)	-	0.63" (15.9 mm)	108-9220	-	-	-	X*	X
CROSS MAX								

*Only available on GA 30/60 models

TITAN® TINES COMPETITIVE MODELS

1/2" (12.7 MM) MOUNT					TITAN® Max		Competitive model	
Length	Core dia. (ID)	OD	Part No	Wall	Part No	Core dia. (ID)	Ryan® GA 24/30/60	John Deere®
TITAN QUAD								
4.50" (114.3 mm)	0.32" (8.3 mm)	0.46" (11.6 mm)	112-1316	0.063" (1.6 mm)	112-1322	0.28" (7.1 mm)	X	-
TITAN SOLID ROUND								
4.50" (114.3 mm)	-	0.50" (12.7 mm)	112-1347	-	-	-	X	-
5.50" (139.7 mm)	-	0.25" (6.3 mm)	112-1329	-	-	-	X	-
TITAN SOLID SLICING								
5.00" (127.0 mm)	-	0.63" (15.9 mm)	112-5102	-	-	-	X	-
5/8" (15.8 MM) MOUNT					TITAN® Max		Competitive model	
Length	Core dia. (ID)	OD	Part No	Wall	Part No	Core dia. (ID)	Ryan® GA 24/30/60	John Deere®
TITAN SIDE EJECT								
4.50" (114.3 mm)	0.43" (10.9 mm)	0.56" (14.2 mm)	112-1303	0.058" (1.5 mm)	112-1304	0.38" (9.5 mm)	X	-
TITAN SOLID ROUND								
4.50" (114.3 mm)	-	0.63" (15.9 mm)	112-1348	-	-	-	X	-
TITAN SOLID SLICING								
5.00" (127.0 mm)	-	0.63" (15.9 mm)	112-5103	-	-	-	X	-

*Only available on GA 30/60 models

TITAN® TINES COMPETITIVE MODELS

3/4" (19.0 MM) MOUNT					TITAN® Max		Competitive model	
Length	Core dia. (ID)	OD	Part No	Wall	Part No	Core dia. (ID)	Ryan® GA 24/30/60	John Deere®
TITAN HOLLOW								
4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	108-9128	0.058" (1.5 mm)	108-9139	0.28" (7.1 mm)	X	X
4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	108-9129	0.058" (1.5 mm)	108-9141	0.38" (9.7 mm)	X	X
4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	108-9130	0.058" (1.5 mm)	108-9143	0.48" (12.2 mm)	X	X
5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	108-9132	0.058" (1.5 mm)	-	-	-	-
5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	108-9133	0.058" (1.5 mm)	108-9147	0.38" (9.7 mm)	X*	X
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	108-9134	0.058" (1.5 mm)	108-9149	0.48" (12.2 mm)	X*	X
TITAN HOLLOW EXT. TAPER								
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	114-0551	0.058" (1.5 mm)	114-0553	0.47" (12.0 mm)	X*	X
TITAN SIDE EJECT								
4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	108-9159	0.058" (1.5 mm)	108-9170	0.28" (7.1 mm)	X	-
4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	108-9160	0.058" (1.5 mm)	108-9172	0.38" (9.7 mm)	X	-
4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	108-9161	0.058" (1.5 mm)	108-9174	0.48" (12.2 mm)	X	-
5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	108-9163	0.058" (1.5 mm)	108-9176	0.28" (7.1 mm)	-	X
5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	108-9164	0.058" (1.5 mm)	108-9178	0.38" (9.7 mm)	-	X
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	108-9165	0.058" (1.5 mm)	108-9180	0.47" (12.0 mm)	-	X
TITAN SIDE EJECT EXT. TAPER								
5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	114-0555	0.058" (1.5 mm)	114-0557	0.47" (12.0 mm)		X
TITAN FAIRWAY HD								
5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	108-9260	0.120" (3.0 mm)	-	-	X*	X
5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	108-9261	0.120" (3.0 mm)	-	-	X*	X
TITAN FAIRWAY								
5.75" (146.0 mm)	0.51" (12.95 mm)	0.77" (19.6 mm)	104-9876	0.120" (3.0 mm)	-	-		X
5.75" (146.0 mm)	0.51" (12.95 mm)	0.88" (22.4 mm)	104-9875	0.120" (3.0 mm)	-	-		X
CLASSIC								
4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	66-9140	0.049" (1.2 mm)	-	-	X	X
4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	59-3670	0.049" (1.2 mm)	-	-	X	X
5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	104-0984	0.058" (1.5 mm)	-	-	X*	X
TITAN SOLID ROUND								
4.50" (114.3 mm)	-	0.25" (6.3 mm)	108-9198	-	-	-	X	X
4.50" (114.3 mm)	-	0.30" (7.6 mm)	108-9199	-	-	-	X	X
4.50" (114.3 mm)	-	0.35" (8.9 mm)	108-9200	-	-	-	X	X
4.50" (114.3 mm)	-	0.40" (10.2 mm)	108-9201	-	-	-	X	X
4.50" (114.3 mm)	-	0.50" (12.7 mm)	108-9202	-	-	-	X	X
4.50" (114.3 mm)	-	0.60" (15.2 mm)	108-9203	-	-	-	X	X
5.50" (139.7 mm)	-	0.25" (6.3 mm)	108-9204	-	-	-	X*	X
5.50" (139.7 mm)	-	0.30" (7.6 mm)	108-9205	-	-	-	X*	X
5.50" (139.7 mm)	-	0.35" (8.9 mm)	108-9206	-	-	-	X*	X
5.50" (139.7 mm)	-	0.40" (10.2 mm)	108-9207	-	-	-	X*	X
5.50" (139.7 mm)	-	0.50" (12.7 mm)	108-9208	-	-	-	X*	X
5.50" (139.7 mm)	-	0.60" (15.2 mm)	108-9209	-	-	-	X*	X
5.50" (139.7 mm)	-	0.75" (19.0 mm)	108-9244	-	-	-	X*	X

*Only available on GA 30/60 models

Prices subject to change without notice.

TITAN® TINES COMPETITIVE MODELS

3/4" (19.0 MM) MOUNT – CONTINUED					TITAN® Max		Competitive model	
Length	Core dia. (ID)	OD	Part No	Wall	Part No	Core dia. (ID)	Ryan® GA 24/30/60	John Deere®
TITAN SOLID SLICING								
4.50" (114.3 mm)	-	0.75" (19.0 mm)	108-9239	-	-	-	-	X
5.50" (139.7 mm)	-	0.75" (19.0 mm)	108-9240	-	-	-	-	X*
TITAN CROSS								
4.50" (114.3 mm)	-	0.50" (12.7 mm)	108-9221	-	-	-	-	X
4.50" (114.3 mm)	-	0.75" (19.0 mm)	108-9223	-	-	-	-	X
5.50" (139.7 mm)	-	0.50" (12.7 mm)	108-9224	-	112-1313	-	-	X*
5.50" (139.7 mm)	-	0.75" (19.0 mm)	108-9226	-	-	-	-	X*
TITAN HOLLOW								
4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	108-9190	0.058" (1.5 mm)	-	-	-	X*
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	108-9191	0.058" (1.5 mm)	-	-	-	X*
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	108-9192	0.058" (1.5 mm)	108-9157	0.48" (12.2 mm)	-	X*
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	108-9193	0.058" (1.5 mm)	-	-	-	X*
TITAN SIDE EJECT								
4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	108-9194	0.058" (1.5 mm)	-	-	-	X*
4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	108-9195	0.058" (1.5 mm)	-	-	-	X*
5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	108-9196	0.058" (1.5 mm)	108-9188	0.48" (12.2 mm)	-	X*
5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	108-9197	0.058" (1.5 mm)	-	-	-	X*
TITAN FAIRWAY HD								
5.75" (146.0 mm)	0.640" (16.3 mm)	0.88" (22.2 mm)	108-9264	0.122" (3.1 mm)	-	-	-	X*
5.75" (146.0 mm)	0.640" (16.3 mm)	1.0" (25.4 mm)	108-9265	0.122" (3.1 mm)	-	-	-	X*
TITAN FAIRWAY								
4.75" (120.6 mm)	16.3 mm (.640")	0.88" (22.2 mm)	92-7941	0.122" (3.1 mm)	-	-	-	X
5.75" (146.0 mm)	16.3 mm (.640")	0.88" (22.2 mm)	92-7900	0.122" (3.1 mm)	-	-	-	

QUICK REFERENCE

Mount	Length	ID	OD	Wall thickness	Part No	Titan® Max part No
TITAN Quad and Max Quad						
½" (12.7 mm)	4.50" (114.3 mm)	0.32" (8.3 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	112-1316	–
¾" (9.5 mm)	4.50" (114.3 mm)	0.25" (6.3 mm)	0.36" (9.1 mm)	0.052" (1.3 mm)	108-9104	108-9112
¾" (9.5 mm)	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	108-9105	108-9114
¾" (9.5 mm)	4.50" (114.3 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	108-9106	108-9116
¾" (9.5 mm)	4.50" (114.3 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	108-9293	–
¾" (9.5 mm)	5.00" (127.0 mm)	0.25" (6.3 mm)	0.55" (14.0 mm)	0.052" (1.3 mm)	138-5937	108-9120
¾" (9.5 mm)	5.00" (127.0 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	137-6526	108-9122
¾" (9.5 mm)	5.00" (127.0 mm)	0.41" (10.3 mm)	0.55" (13.9 mm)	0.063" (1.6 mm)	137-6527	108-9124
¾" (9.5 mm)	5.00" (127.0 mm)	0.48" (12.2 mm)	0.58" (14.7 mm)	0.049" (1.2 mm)	137-6529	–
¾" (9.5 mm)	5.50" (139.7 mm)	0.41" (10.3 mm)	0.58" (14.7 mm)	0.063" (1.6 mm)	108-9290	–
⅝" (15.9 mm)	4.50" (114.3 mm)	0.32" (8.1 mm)	0.46" (11.6 mm)	0.063" (1.6 mm)	112-1332	112-1338
TITAN Hollow and Max Hollow						
¾" (19.0 mm)	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9128	108-9139
¾" (19.0 mm)	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9129	108-9141
¾" (19.0 mm)	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9130	108-9143
¾" (19.0 mm)	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9132	–
¾" (19.0 mm)	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9133	108-9147
¾" (19.0 mm)	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9134	108-9149
¾" (19.0 mm)	6.50" (165.1 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9138	108-9135
¾" (19.0 mm)	6.50" (165.1 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9136	108-9151
¾" (19.0 mm)	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9137	108-9153
⅞" (22.2 mm)	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9190	–
⅞" (22.2 mm)	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9191	–
⅞" (22.2 mm)	5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9192	–
⅞" (22.2 mm)	5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9193	–
TITAN Hollow Extended Taper and Max Extended Taper						
¾" (19.0 mm)	5.75" (146.0 mm)	0.47" (11.9 mm)	0.68" (17.3 mm)	0.058" (1.5 mm)	114-0553	–
¾" (19.0 mm)	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0551	114-0553
¾" (19.0 mm)	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0550	–
TITAN Side Eject and Max Side Eject						
¾" (19.0 mm)	4.75" (120.6 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9159	108-9170
¾" (19.0 mm)	4.75" (120.6 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9160	108-9172
¾" (19.0 mm)	4.75" (120.6 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9161	108-9174
¾" (19.0 mm)	5.75" (146.0 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9163	108-9176
¾" (19.0 mm)	5.75" (146.0 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9164	108-9178
¾" (19.0 mm)	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9165	108-9180
¾" (19.0 mm)	6.50" (165.1 mm)	0.28" (7.1 mm)	0.46" (11.7 mm)	0.058" (1.5 mm)	108-9162	108-9166
¾" (19.0 mm)	6.50" (165.1 mm)	0.41" (10.3 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	108-9167	108-9182
¾" (19.0 mm)	6.50" (165.1 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9168	108-9184
⅝" (15.9 mm)	4.50" (114.3 mm)	0.43" (12.7 mm)	0.56" (14.2 mm)	0.058" (1.5 mm)	112-1303	–
⅞" (22.2 mm)	4.75" (120.6 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9194	–
⅞" (22.2 mm)	4.75" (120.6 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9195	–
⅞" (22.2 mm)	5.75" (146.0 mm)	0.51" (13.0 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	108-9196	108-9188
⅞" (22.2 mm)	5.75" (146.0 mm)	0.63" (16.0 mm)	0.76" (19.3 mm)	0.058" (1.5 mm)	108-9197	–
TITAN Side Eject Extended Taper and Extended Taper Max						
¾" (19.0 mm)	5.75" (146.0 mm)	0.53" (13.4 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	114-0555	114-0557

QUICK REFERENCE

Mount	Length	ID	OD	Wall thickness	Part No	Titan® Max part No
<i>Pro Classic Hollow</i>						
¾" (19.0 mm)	4.75" (120.6 mm)	0.40" (10.2 mm)	0.50" (12.7 mm)	0.049" (1.2 mm)	66-9140	—
¾" (19.0 mm)	4.75" (120.6 mm)	0.50" (12.7 mm)	0.63" (15.9 mm)	0.049" (1.2 mm)	59-3670	—
¾" (19.0 mm)	5.75" (146.0 mm)	0.51" (12.9 mm)	0.63" (15.9 mm)	0.058" (1.5 mm)	104-0984	—
¾" (19.0 mm)	6.50" (165.1 mm)	0.39" (9.9 mm)	0.66" (16.8 mm)	0.058" (1.5 mm)	105-1180	—
⅜" (22.2 mm)	4.75" (120.6 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	62-4600	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.60" (15.2 mm)	0.75" (19.0 mm)	0.065" (1.7 mm)	86-9720	—
<i>TAN Fairway</i>						
¾" (19.0 mm)	5.75" (146.0 mm)	0.51" (12.9 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	104-9876	—
¾" (19.0 mm)	5.75" (146.0 mm)	0.51" (12.9 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	104-9875	—
⅜" (22.2 mm)	4.75" (120.6 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7941	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	92-7900	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	1.0" (25.4 mm)	0.120" (3.0 mm)	104-9877	—
<i>TAN HD Fairway</i>						
¾" (19.0 mm)	5.75" (146.0 mm)	0.51 (12.95 mm)	0.77" (19.6 mm)	0.120" (3.0 mm)	108-9260	—
¾" (19.0 mm)	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	108-9261	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.122" (3.1 mm)	108-9264	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	1.0" (25.4 mm)	0.122" (3.1 mm)	108-9265	—
<i>TAN Split Tine</i>						
¾" (19.0 mm)	5.75" (146.0 mm)	0.51 (12.95 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5121	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	0.88" (22.4 mm)	0.120" (3.0 mm)	112-5122	—
⅜" (22.2 mm)	5.75" (146.0 mm)	0.64" (16.1 mm)	0.92" (23.4 mm)	0.120" (3.0 mm)	112-5123	—
<i>TAN Solid Round</i>						
½" (12.7 mm)	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	112-1347	—
½" (12.7 mm)	5.00" (127.0 mm)	—	0.25" (6.3 mm)	—	112-1329	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9198	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9199	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.35" (8.9 mm)	—	108-9200	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.40" (10.2 mm)	—	108-9201	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.50" (12.7 mm)	—	108-9202	—
¾" (19.0 mm)	4.50" (114.3 mm)	—	0.60" (15.2 mm)	—	108-9203	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.25" (6.3 mm)	—	108-9204	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.30" (7.6 mm)	—	108-9205	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.35" (8.9 mm)	—	108-9206	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.40" (10.2 mm)	—	108-9207	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.50" (12.7 mm)	—	108-9208	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.60" (15.2 mm)	—	108-9209	—
¾" (19.0 mm)	5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9244	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.30" (7.6 mm)	—	108-9210	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.35" (8.9 mm)	—	108-9211	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.40" (10.2 mm)	—	108-9212	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.50" (12.7 mm)	—	108-9213	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.60" (15.2 mm)	—	108-9214	—
¾" (19.0 mm)	6.50" (165.1 mm)	—	0.75" (19.0 mm)	—	108-9245	—
⅜" (9.5 mm)	4.50" (114.3 mm)	—	0.20" (5.1 mm)	—	108-9230	—
⅜" (9.5 mm)	4.50" (114.3 mm)	—	0.25" (6.3 mm)	—	108-9231	—
⅜" (9.5 mm)	4.50" (114.3 mm)	—	0.30" (7.6 mm)	—	108-9232	—
⅜" (9.5 mm)	4.50" (114.3 mm)	—	0.38" (9.7 mm)	—	108-9233	—
⅜" (9.5 mm)	5.50" (139.7 mm)	—	0.20" (5.1 mm)	—	108-9234	—
⅜" (9.5 mm)	5.50" (139.7 mm)	—	0.25" (6.3 mm)	—	108-9235	—
⅜" (9.5 mm)	5.50" (139.7 mm)	—	0.30" (7.6 mm)	—	108-9236	—
⅜" (9.5 mm)	5.50" (139.7 mm)	—	0.38" (9.7 mm)	—	108-9237	—
⅜" (15.9 mm)	4.50" (114.3 mm)	—	0.63" (15.9 mm)	—	112-1348	—
⅜" (22.2 mm)	5.50" (139.7 mm)	—	0.75" (19.0 mm)	—	108-9246	—
⅜" (22.2 mm)	5.50" (139.7 mm)	—	0.88" (22.2 mm)	—	108-9247	—
⅜" (22.2 mm)	6.50" (165.1 mm)	—	0.75" (19.0 mm)	—	108-9248	—
⅜" (22.2 mm)	6.50" (165.1 mm)	—	0.88" (22.2 mm)	—	108-9249	—

QUICK REFERENCE

Mount	Length	ID	OD	Wall thickness	Part No	Titan® Max part No
TITAN Solid Slicing						
½" (12.7 mm)	5.00" (127.0 mm)	–	0.63" (15.9 mm)	–	112-5102	–
¾" (19.0 mm)	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9239	–
¾" (19.0 mm)	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9240	–
¾" (19.0 mm)	6.50" (165.1 mm)	–	0.75" (19.0 mm)	–	108-9241	–
¾" (9.5 mm)	5.00" (127.0 mm)	–	0.63" (15.9 mm)	–	108-9238	–
¾" (15.9 mm)	5.00" (127.0 mm)	–	0.63" (15.9 mm)	–	112-5103	–
¾" (22.2 mm)	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9242	–
¾" (22.2 mm)	6.50" (165.1 mm)	–	0.75" (19.0 mm)	–	108-9243	–
TITAN Cross and Max Cross						
¾" (19.0 mm)	4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9221	–
¾" (19.0 mm)	4.50" (114.3 mm)	–	0.75" (19.0 mm)	–	108-9223	–
¾" (19.0 mm)	5.50" (139.7 mm)	–	0.50" (12.7 mm)	–	108-9224	112-1313
¾" (19.0 mm)	5.50" (139.7 mm)	–	0.75" (19.0 mm)	–	108-9226	–
¾" (19.0 mm)	6.50" (165.1 mm)	–	0.50" (12.7 mm)	–	108-9227	112-1314
¾" (19.0 mm)	6.50" (165.1 mm)	–	0.62" (15.7 mm)	–	108-9228	–
¾" (19.0 mm)	6.50" (165.1 mm)	–	0.75" (19.0 mm)	–	108-9229	–
¾" (9.5 mm)	4.50" (114.3 mm)	–	0.38" (9.5 mm)	–	108-9215	–
¾" (9.5 mm)	4.50" (114.3 mm)	–	0.50" (12.7 mm)	–	108-9216	112-1310
¾" (9.5 mm)	4.50" (114.3 mm)	–	0.62" (15.7 mm)	–	108-9217	–
¾" (9.5 mm)	5.50" (139.7 mm)	–	0.38" (9.5 mm)	–	108-9218	–
¾" (9.5 mm)	5.50" (139.7 mm)	–	0.50" (12.7 mm)	–	108-9219	112-1311
¾" (9.5 mm)	5.50" (139.7 mm)	–	0.62" (15.7 mm)	–	108-9220	–
¾" (22.2 mm)	5.50" (139.7 mm)	–	0.88" (22.2 mm)	–	108-9259	–
TITAN Needle						
Needle	6.43" (163.3 mm)	–	0.188" (4.8 mm)	–	100-3620	–
Needle	7.38" (187.45 mm)	–	0.313" (7.9 mm)	–	100-3621	–
Needle	5.43" (137.9 mm)	–	5.0 mm	–	100-3319	–

QUICK REFERENCE

Mount	Length	ID	OD	Wall thickness	Part No	Titan® Max part No
ProCore SR Series Deep Tine Aerators						
½" (7.9 mm)	10.00" (254.0 mm)	–	0.31" (7.9 mm)	–	SGS0813	–
½" (7.9 mm)	8.50" (215.9 mm)	–	0.31" (7.9 mm)	–	SGS07313	–
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	–	139-8620	–
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	–	139-8624	–
12.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.81" (20.6 mm)	–	139-8613	–
12.0 mm	10.75" (273.1 mm)	–	0.47" (12.0 mm)	–	SGS10504	–
12.0 mm	12.25" (311.2 mm)	–	0.47" (12.0 mm)	–	SGS10500	–
12.0 mm	14.25" (361.9 mm)	–	0.47" (12.0 mm)	–	SGS12500	–
12.0 mm	16.25" (412.8 mm)	–	0.47" (12.0 mm)	–	SGS14500	–
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	–	139-8623	–
12.0 mm	7.00" (177.8 mm)	0.52" (13.2 mm)	0.69" (17.4 mm)	–	139-8614	–
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	–	139-8625	–
12.0 mm	7.00" (177.8 mm)	0.56" (14.2 mm)	0.81" (20.7 mm)	–	139-8615	–
12.0 mm	8.00" (203.2 mm)	–	0.47" (12.0 mm)	–	SGS08500	–
18.0 mm	10.00" (254.0 mm)	0.56" (14.2 mm)	0.75" (19.0 mm)	–	139-8623	–
18.0 mm	10.00" (254.0 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	–	139-8617	–
18.0 mm	10.00" (254.0 mm)	0.76" (19.3 mm)	1.00" (25.4 mm)	–	139-8619	–
18.0 mm	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	–	139-8627	–
18.0 mm	12.25" (311.2 mm)	–	0.71" (18.0 mm)	–	SGS10750	–
18.0 mm	12.50" (317.5 mm)	–	0.88" (22.2 mm)	–	SGS10875	–
18.0 mm	14.00" (355.6 mm)	–	0.88" (22.2 mm)	–	SGS12875	–
18.0 mm	14.25" (361.9 mm)	–	0.71" (18.0 mm)	–	SGS12750	–
18.0 mm	16.00" (406.4 mm)	–	0.88" (22.2 mm)	–	SGS14875	–
18.0 mm	16.25" (412.8 mm)	–	0.71" (18.0 mm)	–	SGS14750	–
18.0 mm	8.00" (203.2 mm)	0.74" (18.8 mm)	1.06" (26.9 mm)	–	139-8628	–
18.0 mm	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	–	139-8622	–
¾" (9.5 mm)	10.75" (273.1 mm)	–	0.38" (9.5 mm)	–	SGS10374	–
¾" (9.5 mm)	12.25" (311.2 mm)	–	0.38" (9.5 mm)	–	SGS10375	–
¾" (9.5 mm)	5.50" (139.7 mm)	0.38" (9.5 mm)	0.50" (12.7 mm)	–	139-8618	–
¾" (9.5 mm)	9.00" (228.6 mm)	–	0.38" (9.5 mm)	–	SGS08375	–
¾" (22.2 mm)	12.00" (304.8 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	–	139-8621	–
¾" (22.2 mm)	12.50" (317.5 mm)	–	0.88" (22.2 mm)	–	SGS10876	–
¾" (22.2 mm)	14.00" (355.6 mm)	–	0.88" (22.2 mm)	–	SGS12876	–
¾" (22.2 mm)	17.88" (454.2 mm)	–	1.00" (25.4 mm)	–	SGS16100	–
¾" (22.2 mm)	8.00" (203.2 mm)	0.94" (23.9 mm)	1.31" (33.3 mm)	–	139-8626	–



PROTECT YOUR INVESTMENT. KEEP IT 100% TORO®.

OUR PROMISE TO YOU

To best protect your investment and maintain optimal performance of your turf equipment, count on Toro genuine parts. When it comes to reliability, Toro delivers replacement parts designed to the exact engineering specifications of our equipment. For peace of mind, insist on Toro genuine parts.

TORO PROVIDES:

- **Industry-leading fill rates** – Your local channel partner, supported by Toro's parts network, offers the parts you need when you need them.
- **Part availability** – **Most local channel partners deliver parts within 24 hours.** Toro backs this promise with **48-hour delivery support**.
- **Competitive pricing** – Toro parts are comparable to will-fit providers.
- **Quality** – Genuine Toro service parts are the same parts used on the original equipment, ensuring maximum performance with less downtime.
- **Unparalleled customer service** – Count on dedicated support for your Toro parts needs.
- **Peace of mind** – With genuine Toro parts, you get the right part with the correct specifications. There's no need to wonder if the part will work.



TORO PROTECTION PLUS™ EXTENDED PROTECTION PLAN

Run your maintenance budget at peak efficiency

The Toro Protection Plus™ (TPP) Extended Protection Plan eliminates the hit that your maintenance budget can take when the unforeseen happens. Coverage is available for new equipment, pre-owned equipment and most Toro attachments and accessories. Just choose the plan that fits your needs.

\$0 deductible for parts and labour on covered repairs | Remaining coverage is transferrable if ownership changes

TORO

Learn More: toro.com/tpp



WHEN WE SAY COUNT ON IT, WE MEAN IT

Every product that carries the Toro brand is backed by over 100 years of history, innovation and timeless dependability. We never stop investing in research and development to give our customers the latest features. That's why Toro is one of the best-known, most trusted brands in the business. We also stand behind our products with a global network of knowledgeable dealers for parts and service support.

Real people. Real support.

Smart features. Proven dependability.

TORO®

Count on it.



toro.com
Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (+1) 952 888 8801
Fax: (+1) 952 887 8258

©2023 The Toro Company.
All rights reserved.
Printed in the USA

23-804-GB

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your distributor for details on all our warranties.



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope