



BAILOY GTI PC CONTROL SYSTEM

Ideal for medium to large Golf Clubs and sites that require greater control and interaction with their irrigation system.

Available in a 2 wire Gemini version or 3 wire Trident version, GTI-PC can have up to 4 DOU's (Decoder Output Units) linked together with 4 control cable outputs (CSG'S) on each one. Each CSG can control up to 114 stations (109 on Gemini) allowing control of up to 1792 stations on Trident and 1744 on Gemini.

- Gemini is ideal for replacing older controllers such as the Watermation TW1 and TW2 and in most cases can utilise existing field hardware.
- Trident is an ideal replacement for the SC3000, CDS DIU. Both these controllers were designed and manufactured by Bailoy therefore can utilise all the existing field cables, decoders and solenoids.

GTI systems can also be used with most major manufacturers sprinklers allowing sites to choose the most economic or suitable types rather than being tied to one manufacturer if using their controller.

GTI-PC uses multiple CSG's, which is better than single control cable systems as a damaged CSG would mean you only loose a small section of the system, not everything



System Features:

GTI PC GEMINI	GTI PC TRIDENT
For use on sites with 2-core control cables	For use on sites with 3-core control cables
Suitable for retro fitting by utilising existing control cables	Suitable for retro fitting by utilising existing control cables
109 stations per control cable	114 stations per control cable
Up to 16 separate control cables (CSGs)	Up to 16 separate control cables (CSGs)
Built-in decoder programmer – programme, read and check decoders from DOU using GTI software	Built-in decoder programmer – programme, read and check decoders from DOU using GTI software
Built-in pump start volt-free contact	Built-in volt-free pump start contact
Rain switch input – turn off irrigation when there is too much rainfall	Rain switch input – turn off irrigation when there is too much rainfall
Alarm sensor inputs – used to detect low system pressure and low tank level	Alarm sensor inputs – used to detect low system pressure and low tank level
Built-in surge protection	Built-in surge protection
LED indicators for instant DOU status	LED indicators for instant DOU status
Compatible with all Bailoy manufactured Gemini and Watermation TW1 and TW2 decoders	Compatible with all Bailoy manufactured Trident, SC3000 and CDS decoders
Available in multiple languages	Available in multiple languages



QUALITY BRANDS, EXCEPTIONAL SERVICE.

