

TORO

Greensmaster® 1018/1021/1026

WALK GREENSMOWERS

FEATURES

Greensmaster 1018/1021/1026

Common Features:

- Heavy-duty, 3.5 hp (2.6 kW) Honda® engine for optimal power
- Telescoping loop handle design with combined operational and safety bail
- Operational bail allows slowing down or a complete stop in tight turns without disengaging traction
- Rubber-mounted handle to reduce oscillation motion from walking for cutting consistency
- No greasing requirement and modular designs for labor saving maintenance
- Choice of cutting units (8, 11 and 14-blade) to accommodate different cutting heights
- Conversion capability from greens to tee mower
- Excellent balance for superior tracking and easy turn around
- Squeeze service / parking brake for enhanced control

Greensmaster 1018:

- 18-inch (45.7 cm) width of cut
- Narrow mowing swath for narrow striping and superior ground-following over undulations
- Choose 11-blade or 14-blade reel provides a smooth, consistent cut resulting in superior ball roll

Greensmaster 1021:

- 21-inch (53.3 cm) width of cut
- Superior quality of cut and reliable performance
- Choose 8-blade, 11-blade or 14-blade reel for superior performance in any mowing condition

Greensmaster 1026:

- 26-inch (66 cm) width of cut
- Wider mowing swath for increased productivity
- Choose 8-blade, 11-blade or 14-blade reel for superior performance in any mowing condition

A new legend in greens mowing is born.

The new Toro® Greensmaster® Fixed-Head Series (1018/1021/1026) has a cutting width range of 18", 21" and 26", respectively. The new design synchronizes the operator and the machine, in an effort to eliminate operator error. All models in the line boast new innovative operator controls; its main feature is a telescoping loop handle that each operator can adjust in seconds to their personal size for comfort and reduce fatigue, which ensures a consistent, pristine cut. These units are designed for minimal maintenance and a long and productive life, to save labor and operation cost.



EdgeSeries™ Reels



Greensmaster® 1018 Specifications*

| GREENSMaster 1018, MODEL 04820 | |
|------------------------------------|--|
| ENGINE | Honda GX120 - 3.5 hp (2.6 kW) @3600 rpm, gasoline with integral lighting coil. |
| FUEL CAPACITY | 2.1 qts (2L) |
| FRAME | Fully modular design allows quick disassembly for service / maintenance of all major components. |
| TRACTION DRIVE | Full gear drive transmission with integral traction differential and traction drive disconnect to ease movement during service / maintenance operations. Interchangeable drum drive gear cases. |
| TRACTION DRUM | Dual position traction drum with positions for contour following or forward weight bias at higher heights of cut. |
| GROUND SPEED | Mowing Speed: 2.0 mph (3.2 km/h) to 3.5 mph (5.6 km/h) Transport Speed: 5.3 mph (8.5 km/h) |
| CLUTCH | Externally-mounted two sided dry disc clutch actuated by dual motion bail. |
| BRAKE | Service / parking – band type. |
| CUTTING UNIT DRIVE | Quick change dual speed gear drive. |
| CUTTING UNIT ATTACHMENT | Detachable cutting unit allows easy removal for service / maintenance or cutting unit exchange for different uses. |
| CUTTING UNIT OPTIONS | 11-blade cutting unit 14-blade cutting unit |
| CONTROLS | Engine mounted: recoil starter, choke, fuel shutoff. Handle mounted: on/off switch, throttle lever, dual motion traction / safety bail, reel engage lever, service/park brake lever, hour meter, light switch (optional). |
| HANDLE | Loop handle with telescoping adjustment with 5" (12.7 cm) total travel, rubber isolated to minimize operator influence during mowing. |
| TRANSPORT TIRES / KICKSTAND | Optional – Two, quick-detachable pneumatic tires (3.00X3.25-6). Kickstand is standard. |
| WIDTH OF CUT | 18" (45.7 cm) |
| HEIGHT OF CUT RANGE | For Greens: Drum Position One: 0.062" to 0.312" (1.5 mm to 8 mm) For Tees: Drum Position Two: 0.25" to .0625" (6 mm to 16 mm) High Height of Cut Kit: 1.18" (30 mm) |
| WEIGHT | 210 lbs (95.2 kg) with 11-blade cutting unit, aluminum Wiehle roller. |
| MAINTENANCE REQUIREMENTS | No daily greasing required. |
| CERTIFICATION | Designed in accordance to applicable ANSI and CE specifications. |
| WARRANTY | Two-year limited warranty. Refer to the Operator's Manual for further details. |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.





Greensmaster® 1021 Specifications*

| GREENSMaster 1021, MODEL 04830 | |
|------------------------------------|--|
| ENGINE | Honda GX120 - 3.5 hp (2.6 kW) @3600 rpm, gasoline with integral lighting coil. |
| FUEL CAPACITY | 2.1 qts (2L) |
| FRAME | Fully modular design allows quick disassembly for service / maintenance of all major components. |
| TRACTION DRIVE | Full gear drive transmission with integral traction differential and traction drive disconnect to ease movement during service / maintenance operations. Interchangeable drum drive gear cases. |
| TRACTION DRUM | Dual position traction drum with positions for contour following or forward weight bias at higher heights of cut. |
| GROUND SPEED | Mowing Speed: 2.0 mph (3.2 km/h) to 3.5 mph (5.6 km/h) Transport Speed: 5.3 mph (8.5 km/h) |
| CLUTCH | Externally-mounted two sided dry disc clutch actuated by dual motion bail. |
| BRAKE | Service / parking – band type. |
| CUTTING UNIT DRIVE | Quick change dual speed gear drive. |
| CUTTING UNIT ATTACHMENT | Detachable cutting unit allows easy removal for service / maintenance or cutting unit exchange for different uses. |
| CUTTING UNIT OPTIONS | 8-blade cutting unit 11-blade cutting unit 14-blade cutting unit |
| CONTROLS | Engine mounted: recoil starter, choke, fuel shutoff. Handle mounted: on/off switch, throttle lever, dual motion traction / safety bail, reel engage lever, service/park brake lever, hour meter, light switch (optional). |
| HANDLE | Loop handle with telescoping adjustment with 5" (12.7 cm) total travel, rubber isolated to minimize operator influence during mowing. |
| TRANSPORT TIRES / KICKSTAND | Optional – Two, quick-detachable pneumatic tires (3.00X3.25-6). Kickstand is standard. |
| WIDTH OF CUT | 21" (53.3 cm) |
| HEIGHT OF CUT RANGE | For Greens: Drum Position One: 0.062" to 0.312" (1.5 mm to 8 mm) For Tees: Drum Position Two: 0.25" to .0625" (6 mm to 16 mm) High Height of Cut Kit: 1.18" (30 mm) |
| WEIGHT | 224 lbs (100 kg) with 11-blade cutting unit, aluminum Wiehle roller. |
| MAINTENANCE REQUIREMENTS | No daily greasing required. On board backlapping available with optional kit. |
| CERTIFICATION | Designed in accordance to applicable ANSI and CE specifications. |
| WARRANTY | Two-year limited warranty. Refer to the Operator's Manual for further details. |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.





Greensmaster® 1026 Specifications*

| GREENSMaster 1026, MODEL 04840 | |
|------------------------------------|--|
| ENGINE | Honda GX120 - 3.5 hp (2.6 kW) @3600 rpm, gasoline with integral lighting coil. |
| FUEL CAPACITY | 2.1 qts (2L) |
| FRAME | Fully modular design allows quick disassembly for service / maintenance of all major components. |
| TRACTION DRIVE | Full gear drive transmission with integral traction differential and traction drive disconnect to ease movement during service / maintenance operations. Interchangeable drum drive gear cases. |
| TRACTION DRUM | Dual position traction drum with positions for contour following or forward weight bias at higher heights of cut. |
| GROUND SPEED | Mowing Speed: 2.0 mph (3.2 km/h) to 3.5 mph (5.6 km/h) Transport Speed: 5.3 mph (8.5 km/h) |
| CLUTCH | Externally-mounted two sided dry disc clutch actuated by dual motion bail. |
| BRAKE | Service / parking – band type. |
| CUTTING UNIT DRIVE | Quick change dual speed gear drive. |
| CUTTING UNIT ATTACHMENT | Detachable cutting unit allows easy removal for service / maintenance or cutting unit exchange for different uses. |
| CUTTING UNIT OPTIONS | 8-blade cutting unit 11-blade cutting unit 14-blade cutting unit |
| CONTROLS | Engine mounted: recoil starter, choke, fuel shutoff. Handle mounted: on/off switch, throttle lever, dual motion traction / safety bail, reel engage lever, service/park brake lever, hour meter, light switch (optional). |
| HANDLE | Loop handle with telescoping adjustment with 5" (12.7 cm) total travel, rubber isolated to minimize operator influence during mowing. |
| TRANSPORT TIRES / KICKSTAND | Optional – Two, quick-detachable pneumatic tires (3.00X3.25-6). Kickstand is standard. |
| WIDTH OF CUT | 26" (66 cm) |
| HEIGHT OF CUT RANGE | For Greens: Drum Position One: 0.062" to 0.312" (1.5 mm to 8 mm) For Tees: Drum Position Two: 0.25" to .0625" (6 mm to 16 mm) High Height of Cut Kit: 1.18" (30 mm) |
| WEIGHT | 240 lbs (108.8 kg) with 11-blade cutting unit, aluminum Wiehle roller. |
| MAINTENANCE REQUIREMENTS | No daily greasing required. On board backlapping available with optional kit. |
| CERTIFICATION | Designed in accordance to applicable ANSI and CE specifications. |
| WARRANTY | Two-year limited warranty. Refer to the Operator's Manual for further details. |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

