TRANZ-FORMER TURF ROLLER




FIELDS GROUNDS TURF SURFACES



The Tranz-Former is a turf roller designed for sports fields, athletic grounds, and large turf areas. It smooths surfaces without changing contours, reduces divots, and enhances field consistency. On sports fields, it minimizes uneven areas and reduces injury risk, helping maintain optimal playing conditions.

Features include a 10-foot rolling width, three articulating water-fillable rolls, a 37HP EFI engine, and a hydraulic system to ensure efficient and consistent turf performance.



Self Contained, No Trailer Needed – Increases efficiency by 35% over traditional rollers with seamless drive, roll, and transport functionality.

Three Drive Oscillating Rolls – Maintains traction and even pressure across contours for a smooth, stress-free roll.

Electric Over Hydraulic Tire System – Effortlessly raises or lowers wheels for fast mode changes, with powered wheels for added traction and control.



10' Rolling Swath

10' rolling swath covers large areas quickly and efficiently. Three articulating driven rolls maintain consistent ground contact for a smooth, creasefree finish.



37HP B&S Engine

The Briggs & Stratton 37 HP EFI Electric Start engine delivers powerful, reliable performance with improved fuel efficiency and easy electric starting in all conditions.



Arm Rest Seat

The armrest seat enhances operator comfort with ergonomic support and airride adjustability, reducing fatigue for smoother, more controlled operation over any terrain.



Turf Tires

Four 8.5 x 8.5-8, 6-ply turf tires and electric-hydraulic actuators enable smooth transport and quick mode transitions.

TRANZ-FORMER TURF ROLLER



Product Specifications	
Length	120"in (1305cm)
Width	120"in (1305cm) - 63"in (160cm) in Transport Mode
Height	95"in (241cm)
Standard Equipment	
Engine	37HP Briggs & Stratton, EFI Electric Start Engine
Fuel Tank	(2) 6 Gallon, CARB Approved Fuel Canisters
Controls	Forward/Reverse, Transport and Rolling
Battery	12 Volt, 850CCA Automotive Type
Hour Meter	Standard
Rolling Swath	120"
Steering Wheel	14" Tilt Adjustable Steering Wheel
Drive Rolls	Three (3), 10-3/4" diameter x 40" long, beveled. Can be filled with water for extra weight. Machined to within two thousandths of an inch concentricity.
Speed	0-10 MPH
Brakes	Hydraulic and Mechanical
Hydraulic Components	Hoses: SAE JIC hose ends & fittings. 3,000 P.S.I. operating & 12,000 P.S.I. burst. Motors: Five (5) Eaton Motors. Pump: One (1) three section tandem Hydro-Gear pump.
Hydraulic Tank	15 Gallon Steel Hydraulic Tank
Electric Hydraulic Cylinders	Six (6) Double Action. Two (2) 4" Stroke, Two (2) 6" Stroke and Two (2) 8" Stroke
Traction Drive	All 3 Rolls are Driven
Climbing Traction	Up to 40°
Turning Radius	Approximately 35"
Cross Contamination Prevention Kit	Standard
Seat	Air-Ride Forward/Reverse Slide Adjustable Arm Rest Seat
Tire/Wheel Assemblies	Four (4) 18.5 \times 8.5-8, 6 Ply, turf tires hydraulically operated. Two are drive wheels.
Optional Equipment	
Roller Options	Rear Wheel Extension Kit, Cool Top with Fan, Cool Top without Fan, Pedal Extensions.

