



# Topdresser 2500

This 25 cu. ft. (698 liter) Topdresser gives you precise control and consistently delivers an even application—whether light or heavy topdressing is desired.



TOPDRESSER 2500, MODEL 44507*											
<b>HOPPER CAPACITY</b>	25 cu. ft. (707 liter) or up to 2,050 lbs. (929.8 kg).										
<b>SPREADING WIDTH</b>	60" (152 cm)										
<b>TOPDRESSING SPEED</b>	Variable to desired application rate. 2-8 mph (3.2-12.8 km/h).										
<b>TRANSPORT SPEED</b>	Up to 12 mph (19.3 km/h). Optional brake kit available.										
<b>CONVEYOR BELT</b>	Seamless 60" (152 cm) wide belt, polyester mono-filament interwoven material w/vulcanized PVC "v-pattern" traction surface.										
<b>METERING GATE</b>	Infinitely variable from closed to 3.5" (8.89 cm) opening for light to heavy applications. Flexible edge and spring release.										
<b>CONTROLS</b>	12-volt on/off switch at operator's position to engage conveyor and brush. Metering gate runs full width in front of brush.										
<b>DRIVE</b>	Hydraulic with chain driven pumps. Belt motor with chain reduction. Brush motor direct drive. Electric hydraulic solenoid control to activate topdress motors. Closed loop hydraulic system with charge pump and 25 micron filtration.										
<b>TIRES</b>	(4) 18 x 10.5-8, 4-ply ribbed, high floatation turf tires on oscillating axle sets.										
<b>DIMENSIONS /WEIGHT</b>	<table border="1"> <thead> <tr> <th>Height</th> <th>Width</th> <th>Overall Length</th> <th>Shipping Weight</th> <th>Maximum Weight</th> </tr> </thead> <tbody> <tr> <td>43" (109 cm)</td> <td>72.5" (184 cm)</td> <td>97.5" (247.6 cm)</td> <td>1,454 lbs. (659.5 kg)</td> <td>3,500 lbs. (1,587.5 kg)</td> </tr> </tbody> </table>	Height	Width	Overall Length	Shipping Weight	Maximum Weight	43" (109 cm)	72.5" (184 cm)	97.5" (247.6 cm)	1,454 lbs. (659.5 kg)	3,500 lbs. (1,587.5 kg)
Height	Width	Overall Length	Shipping Weight	Maximum Weight							
43" (109 cm)	72.5" (184 cm)	97.5" (247.6 cm)	1,454 lbs. (659.5 kg)	3,500 lbs. (1,587.5 kg)							
<b>WARRANTY</b>	Two-year limited warranty. Refer to operator's manual for further details.										

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

