



# TORO T5 SERIES ROTOR

**The Toro T5 RapidSet™ Series Rotor is packed with features, including an industry-leading 5" pop-up height, advanced nozzle technology and superior debris-tolerant seal.**

RapidSet™ arc adjustment offers a quick and effortless way to adjust rotor arc settings with no tools required. It works with just a few twists of the nozzle turret.

Turn the head clockwise to set the right arc edge; turn the head counter-clockwise to increase the arc to the desired position.

The arc can be reduced in a similar fashion. A built in 'slip-clutch' protects the gears during adjustment.

The Toro T5 RapidSet rotor can be set in seconds. Engineered to use the slip clutch to adjust the arc, the T5 RapidSet rotor requires NO TOOLS for arc adjustments.

**For installations where convenience and reliability are key, the T5 RapidSet is the only rotor you'll need.**



**Features:**

<b>RAPIDSET® ARC ADJUSTMENT</b>	Arc adjustments from 40° to 360° can be made quickly with a few twists of the nozzle turret - no tools required. The RapidSet slip clutch also provides protection against gear damage from vandalism or abuse.
<b>125MM POP-UP HEIGHT</b>	Easily replaces many competitive units with the same footprint but delivers an extra 25mm of pop-up.
<b>AIRFOIL™ TECHNOLOGY NOZZLES</b>	The T5 RapidSet comes with a full set of 8 standard nozzles (25°) and 4 low angle nozzles (10°) that utilise proprietary Airfoil™ technology, which creates a zone of low pressure just below the main stream to gently guide water downward for unmatched uniformity, without forcefully washing out seeds.
<b>STAINLESS STEEL</b>	The stainless steel riser and nozzle base provide strength and protect the rotor from wear due to vandalism or sandy soil conditions, resulting in fewer replacements of time.
<b>STRONG RUBBER COVER</b>	Heavy-duty rubber cover minimises injuries and reduces liability (black indicates standard, grey indicates RapidSet, lilac indicates effluent).
<b>CHECK VALVE</b>	An optional check valve is available with a hold back strength of 2.1 m of elevation change.
<b>DESIGN FLEXIBILITY</b>	Designed to suit a variety of applications T5 RapidSet rotors are available in Effluent, Shrub and High Pop models.

**Specifications:**

<b>RADIUS</b>	7.6 - 15.2m
<b>FLOW</b>	2.8 - 36.7 Lpm
<b>OPERATING PRESSURE RANGE</b>	170 - 450 kPa (Max. 517 kPa)
<b>TRAJECTORY</b>	25° standard, 10° low angle
<b>POP-UP TO NOZZLE</b>	125mm (lawn), 300mm (high pop)
<b>INLET</b>	20mm
<b>#3.0 NOZZLE</b>	Factory installed
<b>OPTIONS</b>	Check valve, stainless steel riser, effluent

**QUALITY BRANDS, EXCEPTIONAL SERVICE.**

