



Introducing the bold new Toro Z Master[®] and GrandStand[®] Revolution Series commercial mowers.

Developed by Toro, industry-leading HyperCell batteries deliver superior power that devours the lushest of lawns all day long...without bogging down! Built on the same proven Grandstand® and Z Master® chassis and TURBO FORCE® deck that you've trusted for years, the new Revolution Series delivers lower overall cost over the machine's lifetime.

PATENT-PENDING SOFTWARE CONTROLS

To optimize machine feel and response, including speed control

HYPERCELL LITHIUM ION BATTERY ALL-DAY RUNTIME

Toro designed to operate with machinery and meet landscaper needs

DECK RAKE ADJUSTMENT

To optimize runtime and quality of cut



	GRANDSTAND*	Z MASTER"							
	18560	18748	18	752	18	760	18'	765	
POWER SYSTEM			·						
Battery	HyperCell	HyperCell	Нур	HyperCell		HyperCell		HyperCell	
Battery Quantity	8	10	10 1		10		10		
Battery Capacity	18.4 kWh	23.4 kWh	23.4 kWh 23.4 kWh		23.4 kWh		23.4 kWh		
Runtime (hrs)	4 - 7+	4 - 7+	4 - 7+		4 - 7+		4 - 7+		
Charge Time (hrs)	12	6	6		6		6		
Charge Type	1.2 kW 120V	3.3kW 240V Standard 1.2 kW 120V Optional		3.3kW 240V Standard 1.2 kW 120V Optional		3.3kW 240V Standard 1.2 kW 120V Optional		3.3kW 240V Standard 1.2 kW 120V Optional	
TRACTION	·		·						
Transmission	Planetary Gearset	Planetary Gearset Planetary Gearset		y Gearset	Planetar	y Gearset	Planetar	y Gearset	
Motors	Commercial High Torque	Commercial High Torque Commercial H		l High Torque	Commercia	l High Torque	Commercial	High Torque	
MOWING DECKS			·						
Deck Size	52" (132.1 cm)	48" (121.9 cm)	▶ 52" (132.1 cm)	60 " (1	(52.4 cm)	60" (15	2.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE®	7-Gauge TURBO FORCE	7-Gauge Tl	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE		7-Gauge TURBO FORCE	
Deck Depth	5.5" (14 cm)	5.5" (14 cm)	_	5.5" (14 cm)		5.5" (14 cm)		5.5" (14 cm)	
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer	9" (22.9 cm) Diameter Cast Aluminum w/ Blade Reta	9" (22.9 cr	9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer		9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer		9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer	
Cutting Height	1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in .6 cm increments)	1.5" - 5.0" in .25" increment (3.8 – 12.7 cm in .6 cm increme		1.5" - 5.5" in .25" increments (3.8 – 14.0 cm in .6 cm increments)		1.5" - 5.5" in .25" increments (3.8 – 14.0 cm in .6 cm increments)		1.5" - 5.5" in .25" increments (3.8 – 14.0 cm in .6 cm increments)	
Blades	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated St	eel .204" (.5 cm) He	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	Adjustable	Adjustable	Adju	Adjustable		Adjustable		Adjustable	
Electric Deck Lift	N/A	Optional	Optional		Optional		Optional		
Motors	Mid-Mount Commercial High Torque	Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque		Mid-Mount Commercial High Torque	
Rake Adjustment	Yes	Yes	Υ	Yes		Yes		es	
FEATURES									
MyRIDE® Suspension System	N/A	N/A	N	N/A		N/A		▶ Standard	
Operator Seat	N/A	Deluxe Suspension Comfort w/Armrests		Deluxe Suspension Comfort w/Armrests		Deluxe Suspension Comfort w/Armrests		Deluxe Comfort w/Armrests	
Max Traction Unit Speed (advertised)	10 mph (16.1 km/h)	11 mph (17.7 km/h)	11 mph (11 mph (17.7 km/h)		11 mph (17.7 km/h)		11 mph (17.7 km/h)	
Max Traction Speed Control	Yes - 7 speed settings	Yes - 7 speed settings	es - 7 speed settings Yes - 7 speed settings		Yes - 7 speed settings		Yes - 7 speed settings		
Drive Tires	Super Turf 20" x 10" x 10" (50.8 x 25.4 – 25.4 cm)	Super Turf 24" x 9.5" x 12" (61 x 24.1 – 30.5 cm)	24" x 10	Super Turf 24" x 10.5" x 12" (61 x 26.7 – 30.5 cm)		Super Turf 24" x 12" x 12" (61 x 30.5 – 30.5 cm)		Super Turf 24" x 12" x 12" (61 x 30.5 – 30.5 cm)	
Drive Wheels	Black Steel	Black Steel		Black Steel		Black Steel		Black Steel	
	11" x 4" - 5" Flat-Free	13" x 6.5" - 6" Flat-Free			13" x 6.5" - 6" Flat-Free		13" x 6.5" - 6" Flat-Free		
Front Caster Tires	Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)	Semi-Pneumatic (33 x 16.5 – 15.2 cm)	Semi-P	Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)		Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
Technology	Hour Meter, USB	Hour Meter, USB	Hour M	Hour Meter, USB		Hour Meter, USB		Hour Meter, USB	
ROPS Profile / PIN Type	N/A	Square Tube / Pin w/Lanya	d Square Tube /	Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard		Square Tube / Pin w/Lanyard	
Knee Pad	Deluxe Durable	N/A	N	N/A		N/A		N/A	
Operator Platform	Foldable w/Bumper Cushions	N/A	N/A N/A		N/A		N/A		
LED Lights	Standard	Standard	Standard Standard		Standard		Standard		
Parking Brake	Integrated in Transmission Automatic	Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic		Integrated in Transmission Automatic	
Mower Warranty*	5-Year 1200-Hour 2-Year No Hour Limit	5-Year 1500-Hour 2-Year No Hour Limit		5-Year 1500-Hour 2-Year No Hour Limit		5-Year 1500-Hour 2-Year No Hour Limit		5-Year 1500-Hour 2-Year No Hour Limit	
WEIGHTS AND MEASUREME	ENTS								
Weight	1,109 lbs. 503.0 kg	1,354 lbs. 614.2 k	1,367 lbs.	620.1 kg	1,381 lbs.	626.4 kg	1,461 lbs.	662.7 kg	
ROPS Height (Folded)	N/A N/A	46.3" 117.6 cr	ո 46.3"	117.6 cm	46.7"	118.6 cm	49.9"	126.7 cm	
ROPS Height (Upright)	N/A N/A	71.6" 181.9 cr	n 71.6"	181.9 cm	72.1"	183.1 cm	72.1"	183.1 cm	
Deck Clearance Width	53.8" 136.7 cm	52.2" 132.6 cr	n 55.6"	141.2 cm	60.4"	153.4 cm	60.4"	153.4 cm	
Deflector Width	67.8" 172.2 cm	63.1" 160.3 cr	n 67.2"	170.7 cm	75.2"	191.0 cm	75.2"	191.0 cm	
Length (Platform Up)	61.0" 154.9 cm	N/A N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Length (Flation in Op)	,								